

CYDLF4FT

CYDLGF4FT




HIGHLIGHTS

FEATURES

- **CYDLF4FT**: 2 independent Feed-Through Terminals
- **CYDLGF4FT** 2 independent Feed-Through Terminals + Grounding Terminal
- 6mm wide compact design
- 2x2 internal jumper channels
- **Same Profile** as CYDLF Fuse Block and CYDLK Disconnect Block allows jumpers to both Fuse and Disconnect Terminals

APPLICATIONS

- Tight Space Wiring Applications
- Combined Fuse & Disconnect Projects with limited DIN Rail Space



Dimensions & Weight

Width	6 mm	6 mm
Length	94.5 mm	94.5 mm
Height w DIN Rail	35 x 7.5 mm 35 x 15 mm	90.9 mm 98.4 mm
Weight per piece	25.2 g	31.8 g

Technical Data/Ratings

Approvals CE, EX, IECEx, Lloyd's Register, IEC	UL US E220514, C-UL US 60947-7-1, IEC 60947-7-1	UL US E220514, C-UL US 60947-7-1, IEC 60947-7-1
Wire Size (solid / stranded)	24-10 AWG, 0.2-4 mm ²	24-10 AWG, 0.2-4 mm ²
Voltage Rating	300 V, 1000V AC/DC	300 V, 1000V AC/DC
Current Rating Feed Thru (Top)	30 A	30 A
Current Rating Feed Thru (Bottom)	30 A	30 A
Torque	4.5 lb-in, 0.5 Nm	4.5 lb-in, 0.5 Nm
Insulation Material	Polyamide 66	Polyamide 66

Installation Instructions

Wire Stripping Length	9 mm	9 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
Grey (standard)	CYDLF4FT	50	CYDLGF4FT	50
Blue BU	CYDLF4FTBU	50	CYDLGF4FT/BU	50
Black BL	CYDLF4FT/BL	50	CYDLGF4FT/BL	50

Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
DIN Rail	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop	CA702 CA802 CA202	50 50 50	CA702 CA802 CA202	50 50 50
Shorting Link/ Jumpers	2 pole JX4/2 3 pole JX4/3 4 pole JX4/4 5 pole — 6 pole — 7 pole — 8 pole JX4/8 10 pole JX4/10 16 pole JX4/16	100 50 50 — — — 10 10 10	2 pole JX4/2 3 pole JX4/3 4 pole JX4/4 5 pole — 6 pole — 7 pole — 8 pole JX4/8 10 pole JX4/10 16 pole JX4/16	100 50 50 — — — 10 10 10
Marking Tag Warning Label	MT6 WLX4	1 Pk. (100 tags) 1 Pk. (100 tags)	MT6 WLX4	1 Pk. (100 tags) 1 Pk. (100 tags)

Additional colors available.

