Instruction Sheets:

? None Available

CAD Files: (CAD Format & Compression Information)

- 2 3D Model (STEP, Version A)
- ? 3D Model (IGES, Version A)
- ? 2D Drawing (DXF, Version A)

List all Documents

Product Features

(Please use the Product Drawing for all design activity)

Product Type Features:

- ? Signal Routing Type = NIC
- ? PCB Mount Style = Thru Hole
- ? Shielded = Yes
- ? Shield Material = Brass

Mechanical Attachment:

- ? Jack Configuration = 1 x 1
- ? Impedance (?) = 100

Electrical Characteristics:

- ? Component Type = Single Port
- ? <u>Turns Ratio</u> = 1:2

Termination Related Features:

? Bottom Panel Ground Tab = Without

Body Related Features:

- ? LED = With
- ? Shield Panel Ground Tabs = With
- 2 Latch Orientation = Inverted Latch Up
- ? Bottom Shield = Without
- ? Shield Plating = Semi Bright Nickel (Pre plated)

Housing Related Features:

- Housing Flammability Rating = UL 94V -0
- ? Housing Material = Thermoplastic

Configuration Related Featu

- ? Magnetic Circuit = 720
- ? Decoupling Capacitor =
- ? Rear PCB Ground Tab
- ? Signal Lead Quantity = 8

Industry Standards:

- ? RoHS/ELV Compliance compliant
- Lead Free Solder Procest capable to 240°C

Identification Marking:

- 2 Left LED Color (Position ohm resistor
- ? Right LED Color (Position ohm resistor

Conditions for Usage:

? Temperature Rating to +70 °C)

Operation/Application:

? Application = 10BASE

Other:

- ? <u>Insulator</u> = Without
- ? Brand = Transpower

Languages : English | Deutsch | Español | Português (do Brasil) | ??????? | Italiano | ???? (??)

Country Sites : China | Japan

Home | Customer Support | Supplier | Site Map | Privacy Policy | Browser Support

© 2006 Tyco Electronics Corporation All Rights Reserved