

P-DI - Isolating plug

3036783

<https://www.phoenixcontact.com/us/products/3036783>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Isolating plug, depth: 23.1 mm, width: 3.5 mm, height: 10.8 mm, color: orange

Your advantages

- Can be used in all ...-TG disconnect terminal blocks from the CLIPLINE complete system
- The P-DI isolating plug can be easily removed to release the connection and then "parked" back to front in the disconnect zone

Commercial data

Item number	3036783
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE29
Product key	BE2ZWX
Catalog page	Page 415 (C-1-2019)
GTIN	4017918901998
Weight per piece (including packing)	0.634 g
Weight per piece (excluding packing)	0.617 g
Customs tariff number	85366990
Country of origin	CN

P-DI - Isolating plug



3036783

<https://www.phoenixcontact.com/us/products/3036783>

Technical data

Product properties

Product type	Knife
Data management status	
Article revision	04

Dimensions

Width	3.5 mm
Height	10.8 mm
Depth	23.1 mm

Material specifications

Color	orange (RAL 2003)
Flammability rating according to UL 94	V2
Insulating material	PA
Static insulating material application in cold	-40 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (operation)	20 % ... 90 %
Permissible humidity (storage/transport)	30 % ... 70 %

P-DI - Isolating plug



3036783

<https://www.phoenixcontact.com/us/products/3036783>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3036783>



CSA

Approval ID: 2030668

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	15 A	-	-



IECEE CB Scheme

Approval ID: DE1-62955



EAC

Approval ID: RU C-DE.BL08.B.00511



BV

Approval ID: 25278/C1 BV



VDE Zeichengenehmigung

Approval ID: 40037480

	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	-	-	-	0.2 - 4

P-DI - Isolating plug



3036783

<https://www.phoenixcontact.com/us/products/3036783>

Classifications

ECLASS

ECLASS-11.0	27141192
ECLASS-12.0	27141192
ECLASS-13.0	27141192

ETIM

ETIM 9.0	EC004592
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

P-DI - Isolating plug

3036783

<https://www.phoenixcontact.com/us/products/3036783>



Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com