

Search within category

GO

BUY NOW

DESIGN / INSTALL



BGHSTT25

Panduit Thin-wall Heat Shrink Tubing shrinks around wires, connectors, joints and terminals when heated to protect against abrasion. Polyolefin, European, 6.4mm x 8.5m (0.25"D x 27.89'L), Black, 1pc.

Available Only for the European Market

Specs	Packaging Details	Documents	★ Add to Favorites	🛒 Add to BOM
Material	Polyolefin			
Color	Black			
CSA Certified	Yes			
Military Specification	AMS-DTL-23053/5 Class 1 (material performance only)			
UL Recognized	Yes			
Length (m)	8.5			
Flammability Rating	N/A			
Max. Recovered I.D. (In.)	0.125			
Max. Recovered I.D. (mm)	3.2			
Min. Expanded I.D. (In.)	0.250			
Min. Expanded I.D. (mm)	6.4			
Nominal Recovered Wall Thickness (mm)	0.6			
Note	Available Only for the European Market			
Product Type	Heat Shrink			
Shrink Ratio	2:1			
Sub Brand	Dry-Shrink			
Temperature Range	-67°F - 275°F (-55°C - 135°C)			
Type	Thin Wall			
RoHS Compliancy Status	Compliant			
Min. Order Qty.	1			