




Terminals & Splices > Quick Disconnects



Quick Disconnect Terminal Type: **Receptacle**

Wire Size: **.32 – .82 mm²**

Mating Tab Width: **2.8 mm [.11 in]**

Mating Tab Thickness: **.51 mm [.02 in]**

Features

Product Type Features

Insertion Force	Normal
-----------------	--------

Configuration Features

Connection Capacity	Single
Compatible With Wire & Cable Type	Discrete Wire

Contact Features

Quick Disconnect Terminal Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Mating Tab Thickness	.51 mm[.02 in]
Terminal Orientation	Straight
Contact Base Material	Brass
Terminal Plating Material	Unplated
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

--	--



Product Terminates To	Wire & Cable
-----------------------	--------------

Mechanical Attachment

Wire Insulation Support	With
Mating Retention Type	Locking Lance

Dimensions

Terminal Material Thickness	6.35 mm[.25 in]
Product Length	13.97 mm[.55 in]
Compatible Insulation Diameter Range	2.03 – 3.05 mm[.08 – .12 in]
Wire Size	.32 – .82 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	9000
Packaging Method	Strip/Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2150769-1
OCEAN_2.0_Applicator-E-070F140F-REM

TE Part # 2150769-2
OCEAN_2.0_Applicator-E-070F140F-REA

TE Part # 63580-1
FF 125 REC 22-18AWG TPBR

TE Part # 7-2150769-7
OCEAN_2.0_SPARE_PART_KIT-070F140F

Also in the Series | FASTIN-FASTON 110

Automotive Housings(6)

Automotive Terminals(5)

Crimp Terminal Housings(34)

Insertion & Extraction Tools(3)

Quick Disconnects(83)


Customers Also Bought

TE Part #2236721-1
ADAPTER,FOR TAB HOUSING,ASSY

TE Part #292253-8
CT CONN MT HDR ASSY H 8P NAT

TE Part #4-1734592-0
FPC CONN. 0.5MM PITCH B/C, 40P

TE Part #42068-1
110 FASTON REC 22-18 AWG TPBR



TE Part #170015-1
FF 110 REC 20-16AWG BR



TE Part #953122-4
40W MQS COVER ASSY (15d)



TE Part #1622461-1
LR1 1% 3K3



TE Part #1-1718484-1
CARRIER FOR RECEPTACLE INSERTS



TE Part #G-NSDOG1-006
AXISENSE-1 V-OUT-180 TILT SENSOR



TE Part #160743-4
110 FASTIN FASTON, TAB, 20-16 AWG, PTBR

Documents

Product Drawings

FF 110 REC 22-18AWG BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63241-1_V_c-63241-1-v.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Application Specification

English

Application Specification

English

FASTIN-FASTON 110, 187, 205 And 312 Series Receptacle Contacts

English