






RECOMMENDED LAND PATTERN DIMENSION OF PCB (MOUNTING SIDE)
(RECOMMENDED METAL MASK THICKNESS:0.15mm)



- NOTE
- | | |
|---|--|
| 1 | HRS MARK SHALL BE OPTIONAL. |
| 2 | LEAD CO-PLANARITY SHALL BE 0.1mm MAX. |
| 3 | EMBOSSED CARRIER TAPE PACKAGING SHALL BE APPLIED FOR THIS PRODUCT.
SEE NEXT PAGE FOR DETAILS. |
| 4 | THIS PRODUCT HAS TAPE FOR VACUUM PICKUP.
SEE NEXT PAGE FOR DETAIL OF STICKING POSITION, ETC. |
| 5 | FOR MODIFICATION, ETC, PREVENTIVE HOLE FOR SINK MARK MAY BE ADDED ACCORDING TO CIRCUMSTANCES. |
| 6 | THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE. |


2	PHOSPHOR BRONZE	CONTACT AREA:GOLD 0.1μm min.			
		LEAD AREA:GOLD FLASH			
		UNDER PLATING:NICKEL 1μm min.			
1	PPS	LIGHT BROWN (UL94V-0)	5	POLYIMIDE	(TAPE FOR VUCUUM PICKUP)
			4	POLYESTER	(TOP COVER TAPE)
			3	POLYSTYRENE	(EMBOSSD CARRIER TAPE)
NO.	MATERIAL	FINISH , REMARKS	NO.	MATERIAL	FINISH , REMARKS

UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
HIROSE ELECTRIC CO., LTD.		APPROVED	: HS. OKAWA	08.12.15	DRAWING NO. EDC3-084962-23			
		CHECED	: HT. YAMAGUCHI	08.12.15	PART NO. FX6-20P-0.8SV(93)			
		DESIGNED	: SY. KAMIGA	08.12.12	CODE NO. CL576-0001-3-93			
		DRAWN	: HK. SUNADORI	08.12.12				




Jul.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

DRAWING FOR PACKING(2:1)



UNREELING DIRECTION



REEL DIMENSION (FREE)



DETAIL OF TAPE FOR VACUUM PICKUP (5:1)



NOTE 1 1 REEL : 1000 CONNECTORS.
2 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.
3 REMOVE THE VACUUM PICKUP TAPE AFTER MOUNTING THE CONNECTOR.

HRS	DRAWING NO.	EDC3-084962-23
	PART NO.	FX6-20P-0.8SV(93)
	CODE NO.	CL576-0001-3-93