

1

2

4

5

由Autodesk教育版产品制作

1



2

3


4

5

5





WITH COVER




SECTION A-A




- 技术指标:
1. 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象.
 2. 温度范围: -25° C~85° C.
 3. 额定电压: 50V AC,DC.
 4. 耐电压: 500V AC/minute.
 5. 接触电阻: ≤0.02Ω.
 6. 绝缘电阻: ≥100MΩ.
 7. 额定电流: 1A AC,DC.




2~6 Pin



7 Pin



14~16 Pin



序号	品名	材质
①	1.25- H型卧式WTB胶芯	PA6T UL94V-0 米黄色
②	1.25- H型立式WTB端子	铜合金/表面镀锡
③	1.25- H型卧式WTB焊片	铜合金/表面镀锡
④	1.25- H型立式WTB吸盖	LCP UL94V-0 自然色

CKT	A	B	C	D	E	F
2	1.25	3.80	5.75	4.95	2.15	0.75
3	2.50	5.05	7.00	6.20	3.40	2.00
4	3.75	6.30	8.25	7.45	4.65	3.25
5	5.00	7.55	9.50	8.70	5.90	4.50
6	6.25	8.80	10.75	9.95	7.15	5.75
7	7.50	10.05	12.00	11.20	6.65	4.15
8	8.75	11.30	13.25	12.45	6.65	4.15
9	10.00	12.55	14.50	13.70	7.90	5.40
10	11.25	13.80	15.75	14.95	9.15	6.65
11	12.50	15.05	17.00	16.20	10.40	7.90
12	13.75	16.30	18.25	17.45	11.65	9.15
13	15.00	17.55	19.50	18.70	12.90	10.40
14	16.25	18.80	20.75	19.95	11.65	9.15
15	17.50	20.05	22.00	21.20	11.65	9.15
16	18.75	21.30	23.25	22.45	11.65	9.15

深圳市万骏达电子有限公司 http://www.wanjunda.com	
品名 (ITEM NO)	1.25 Pitch H型立式WTB
料号 (PART NO)	WF-GH1.25-nP-WT
模号 (MODEL NO)	

图号 (DWG NO)		单位 (UNIT): MM
版本 (REV)		比例 (SCALE) 1:1
日期 (DATE)		未注公差
设计 (DESIGN)		TOLERANCE UNSPECIFIED
审核 (CHECKED)		X.X ±0.30
核准 (APPROVED)		X.XX ±0.20
		X.XXX ±0.10
		X" ±5°
		X.X" ±2°

由Autodesk教育版产品制作

E

F