




Features


- Maximum Output current I_{OM} : 0.8A
- Output voltage V_O : 15V
- Continuous total dissipation
 P_D : 1.25 W ($T_a = 25^\circ\text{C}$)



Package Marking and Ordering Information

Product ID	Pack	Marking	Qty(PCS)
78M15	TO-252-2L (DPAK)	78M15	2500

Typical Application Circuit



Absolute Maximum Ratings

CHARACTERISTIC	SYMBOL	VALUE	UNIT
Maximum input voltage	V_{IN}	35	V
Maximum junction temperature	$T_{J\text{ Max}}$	150	$^\circ\text{C}$
Storage temperature	T_{stg}	- 65 ~ 150	$^\circ\text{C}$
Soldering temperature & time	T_{solder}	260 $^\circ\text{C}$, 10s	-










Electrical Characteristics

Parameter	Symbol	Test conditions		Min	Typ	Max	Unit
Output Voltage	Vo	$V_i=23V, I_o=350mA$	25°C	14.4	15	15.6	V
		$17.5 \leq V_i \leq 30V, I_o=5mA \sim 350mA$ $P_o \leq 15W$	0-125°C	14.25	15	15.75	V
Load Regulation	ΔV_o	$I_o=5mA \sim 500mA$	25°C			300	mV
		$I_o=5mA \sim 200mA$	25°C			150	mV
Line Regulation	ΔV_o	$17.5V \leq V_i \leq 30V, I_o=200mA$	25°C			100	mV
		$20V \leq V_i \leq 26V, I_o=200mA$	25°C			50	mV
Quiescent Current	Iq	$V_i=23V, I_o=350mA$	25°C			6	mA
Quiescent Current Change	ΔI_q	$17.5V \leq V_i \leq 30V, I_o=200mA$	0-125°C			0.8	mA
	ΔI_q	$V_i=23V, I_o=5mA \sim 350mA$	0-125°C			0.5	mA
Output Noise Voltage	V _N	10Hz ≤ f ≤ 100KHz	25°C		90		μV
Ripple Rejection	RR	$18.5 \leq V_i \leq 28.5V, f=120Hz, I_o=300mA$	0-125°C	54			dB
Dropout Voltage	V _d		25°C		2		V




Typical Characteristics







TO-252-2L(DPAK) Package Information



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	2.200	2.400	0.087	0.094
A1	0.000	0.127	0.000	0.005
b	0.660	0.860	0.026	0.034
c	0.460	0.580	0.018	0.023
D	6.500	6.700	0.256	0.264
D1	5.100	5.460	0.201	0.215
D2	0.483 TYP.		0.190 TYP.	
E	6.000	6.200	0.236	0.244
e	2.186	2.386	0.086	0.094
L	9.800	10.400	0.386	0.409
L1	2.900 TYP.		0.114 TYP.	
L2	1.400	1.700	0.055	0.067
L3	1.600 TYP.		0.063 TYP.	
L4	0.600	1.000	0.024	0.039
Φ	1.100	1.300	0.043	0.051
θ	0°	8°	0°	8°
h	0.000	0.300	0.000	0.012
V	5.350 TYP.		0.211 TYP.	



Attention

- Any and all HUA XUAN YANG ELECTRONICS products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your HUA XUAN YANG ELECTRONICS representative nearest you before using any HUA XUAN YANG ELECTRONICS products described or contained herein in such applications.
- HUA XUAN YANG ELECTRONICS assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein.
- Specifications of any and all HUA XUAN YANG ELECTRONICS products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- HUA XUAN YANG ELECTRONICS CO.,LTD. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all HUA XUAN YANG ELECTRONICS products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of HUA XUAN YANG ELECTRONICS CO.,LTD.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. HUA XUAN YANG ELECTRONICS believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the HUA XUAN YANG ELECTRONICS product that you intend to use.