


REVISIONS					
REV.	ECN NO.	LOCATION	DESCRIPTION	DATE	DESIGN
A0	N/A		INITIAL RELEASE	/	/
A1	N/A		图面升级整理图面	2025.06.26	阿树

Model No.	PJ-326-SMT
Schematic	

Technical characteristics
技术特征
Service condition: -30 ~70°
使用条件: -30 ~70°
Rated load: DC30V 0.5A
额定负载: DC30V 0.5A
Contact resistance: ≤0.03 Ω
接触电阻: ≤0.03 Ω
Insulation resistance: ≥100MΩ DC250V
绝缘电阻: ≥100MΩ DC250V
Pressure: AC500V(50HZ)/min
压力: AC 500v(50HZ)/分钟
Insertion and pulling force: 3~20N
插拔力: 3~20N
Life expectancy: 5000
寿命: 5000

Plastic	PPA	
Terminal 3	Phosphor Bronze	TIN
Terminal 2	Phosphor Bronze	TIN
Terminal 1	Phosphor Bronze	TIN
PAPT NAMF	MATERIAL	PLATING

AuGLAR	±5°
X.	±0.40
X.x	±0.30
X.xx	±0.20
X.xxx	±0.15
UNSPECIFIED TOLERAUCES	



DESIGN	阿树
CHECKED	
APPROVED	

VIEW:	
UNIT:	mm/in
SIZE:	A4

MODEL TYPE:	3.5 PHONE JACK
PART NO.:	PJ-326-SMT
DWG NO.:	

SCALE	PAGE	REVISION
N/A	1/1	A1

XKB INDUSTRIAL PRECISION CO.,LIMITED

