



Product Specification

XBLW UC2845

Current Mode Pulse-width Controller


WEB | www.xinboleic.com



Descriptions

The UC2845 is a fixed frequency current mode PWM controllers. It is specifically designed for Off-Line and DC-DC converter applications. These integrated circuits feature an oscillator, a temperature compensated reference, high gain error amplifier, current sensing comparator, and a high current totem pole output ideally suited for driving a power MOSFET. Also included are protective features consisting of input and reference undervoltage lockouts each with hysteresis, cycle-by-cycle current limiting, a latch for single pulse metering, and a flip-flop which blanks the output off every other oscillator cycle, allowing output deadtimes to be programmed from 50% to 70%. The U2845 is tailored for lower voltage applications having UVLO thresholds of 8.2V (on) and 7.6V (off).

This device is available in SOP-8 package and DIP-8 package.



Feature

- Current Mode Operation to 500 kHz Output Switching Frequency
- Output Deadtime Adjustable from 50% to 70%
- Automatic Feed Forward Compensation
- Latching PWM for Cycle-By-Cycle Current Limiting
- Internally Trimmed Reference with Undervoltage Lockout
- High current push-pull output (drive current up to 1A)
- Undervoltage Lockout with Hysteresis
- Low Startup and Operating Current (< 0.5 mA)


Applications

- Switching regulators of any polarity
- Transformer-coupled DC-DC converters

Ordering Information

Product Model	Package Type	Marking	Packing	Packing Qty
XBLW UC2845AN	DIP-8	UC2845AN	Tube	2000pcs/Box
XBLW UC2845BDTR	SOP-8	UC2845B	Tape	2500pcs/Reel


Pins Description



(Top view)

No.	Name	Symbol	Description
1	Compensation	COMP	Error amplifier compensation pin. Connect external compensation components to this pin to modify the error amplifier output.
2	Voltage Feedback	V _{FB}	Inverting input to the internal error amplifier. VFB is used to control the power converter voltage-feedback loop for stability
3	Current Sense	I _{SENSE}	Primary-side current sense pin. Connect to current sensing resistor. The PWM uses this signal to terminate the OUTPUT switch conduction.
4	Oscillator	R _T / C _T	Connect timing resistor, RRT, to VREF and timing capacitor, CCT, to GROUND from this pin to set the switching frequency and maximum output ratio. Maximum frequency can up to 500kHz .
5	Ground	GND	Ground
6	Output	OUTPUT	OUTPUT is the gate drive for the external MOSFET. Peak currents of up to 1 A are sourced and sunk by this pin.
7	Power Supply	V _{CC}	provides power to the device.
8	Reference Voltage	V _{REF}	VREF is used to provide charging current to the oscillator timing capacitor through the timing resistor.

Simplified Block Diagram



Absolute Maximum Ratings

($T_{amb} = 25^\circ\text{C}$, unless otherwise noted)

Rating	Symbol	Value		Unit
		Min.	Max.	
Power voltage	V_{CC}		30	V
Output Current	I_o	-1	1	A
Output Energy	W		5	μJ
Error Amp Output Sink Current	I_o		10	mA
Current Sense and Voltage Feedback Inputs	V_{in}	-0.3	6.3	V
Operating Junction Temperature	T_j		150	$^\circ\text{C}$
Power Dissipation	P_D		1	W
Operating Ambient Temperature	T_{amb}	-40	85	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-65	150	$^\circ\text{C}$

Electrical Characteristics

($V_{CC}=15V$, $R_T=10k\Omega$, $C_T=3.3nF$, $T_{amb}=-40^{\circ}C \sim 85^{\circ}C$, unless otherwise noted)


Characteristic	Symbol	Test conditions	Min.	Typ.	Max.	Unit
Reference Section						
Reference Output Voltage	V_{REF}	$T_j=25^{\circ}C, I_{REF}=1mA$	4.9	5.00	5.1	V
Line Regulation rate	ΔV_{REF}	$12V \leq V_{CC} \leq 25V$		6	20	mV
Load Regulation	ΔV_{REF}	$1mA \leq I_{REF} \leq 20mA$		6	25	mV
Output Short Circuit Current	I_{sc}	$T_{amb}=25^{\circ}C$	-30	-80	-180	mA
Oscillator Section						
Frequency	f_{osc}	$T_j=25^{\circ}C$	47	52	57	kHz
Frequency Change with Voltage	$\Delta f/\Delta V_{CC}$	$12V \leq V_{CC} \leq 25V$		0.05	1	%
Oscillator Voltage Swing	$V_{(OSC)}$	PIN 4 peak to peak		1.6		Vpp
Discharge Current	I_{dischg}	$T_j=25^{\circ}C$	7.5	8.8	11	mA
Error Amplifier Section (EA)						
Input Bias Current	I_{BIAS}			-0.1	-2	μA
Voltage Feedback Input	$V_{in(EA)}$	$V_{COMP}=2.5V$	2.42	2.52	2.58	V
Open Loop Voltage Gain	G_{VO}	$2V \leq V_O \leq 4V$	60	90		dB
Power Supply Rejection Ratio	PSRR	$12V \leq V_{CC} \leq 25V$	60	70		dB
Output Current – Sink	I_{SINK}	$V_{FB}=2.7V, V_{COMP}=1.1V$	2	6.5		mA
Output Current – Source	I_{SOURCE}	$V_{FB}=2.3V, V_{COMP}=5V$	-0.5	-0.9		mA
Output Voltage Swing (High State)	V_{OH}	$V_{FB}=2.3V, R_L=15k\Omega$ to GND	5	6.4		V
Output Voltage Swing (Low State)	V_{OL}	$V_{FB}=2.7V, R_L=15k\Omega$ to P in 8		0.87	1.1	V

Electrical Characteristics

($V_{CC}=15V, R_T=10k\Omega$, $C_T=3.3nF, T_{amb}=0^{\circ}C \sim 70^{\circ}C$, unless otherwise noted)



Current Sense Section						
Current Sense Input Voltage Gain	G_V		2.85	3	3.15	V/V
Maximum Current Sense Input Threshold	$V_{I(MAX)}$	$V_{COMP}=5V$	0.9	1	1.1	V
Power Supply Rejection Ratio	PSRR	$12V \leq V_{CC} \leq 25V$		70		dB
Input Bias Current	I_{BIAS}			-2	-10	μA
Output Section						
Output Voltage Low State	V_{OL}	$I_{SINK}=20mA$		0.1	0.4	V
		$I_{SINK}=200mA$		1.5	2.2	V
Output Voltage High State	V_{OH}	$I_{SOURCE}=20mA$	13	13.5		V
		$I_{SOURCE}=200mA$	12	13.0		V
Output Voltage Rise Time	t_r	$C_L=1nF$		50	150	ns
Output Voltage Fall Time	t_f	$C_L=1nF$		50	150	ns
Undervoltage Lockout Section						
Startup Threshold	$V_{TH(ST)}$		7.8	8.3	9.0	V
Minimum Operating Voltage After Turn-On	$V_{OPR(MIN)}$		7.0	7.6	8.2	V
PWM Section						
Duty Cycle Maximum	$D (MAX)$		45	48	50	%
Duty Cycle Minimum	$D (MIN)$				0	%
Total Device						
Power Supply Current (Startup)	I_{ST}			0.13	0.5	mA
Power Supply Current(Operating)	$I_{CC(OPR)}$	$V_{SENSE}=V_{FB}=0V$		11	17	mA
Power Supply Zener Voltage	V_Z	$I_{CC}=25mA$		34		V

Basic Test Circuit Diagram




Grounding techniques should be carefully considered when there are high peak currents associated with capacitive loads. The timing and bypass capacitors must be installed next to the PIN5 and single-point grounded. Transistors and 5k Ω potentiometers are used to sample waveforms and send waveforms with adjustable slopes to PIN3.

Undervoltage off (UVLO)




The output driver is placed in a high impedance state when entering an undervoltage shutdown. The sixth pin must be grounded with a leakage resistance to prevent leakage current from pushing the power switch

Error amplifier connection




Error amplifier can push-pull output 0.5 ma current

Current detection circuit



Peak current (I_S) is defined as: $I_S (MAX) \approx 1.0 \text{ V}/R_s$ requires a small RC filter network to suppress the transient response of the switch.

Oscillator waveform and maximum duty cycle, period




The oscillating time capacitor C_T is charged by V_{REF} via R_T and discharged by an internal current source. The internal clock signal drives the output to a low level during discharge. The oscillation period and the maximum duty cycle can be determined by selecting R_T and C_T simultaneously. The time of charge and discharge is determined by the following formula:

$$t_c \approx 0.55 R_T * C_T$$

$$t_d \approx R_T * C_T * \ln\left(\frac{0.063 R_T - 2.7}{0.063 R_T - 4}\right)$$


$$\text{The frequency is: } f = (t_c + t_d)^{-1}$$

$$\text{When: } R_T > 5K\Omega, \quad f \approx \frac{1.8}{R_T * C_T}$$



Electrical time capacitance (nF)


Relationship between oscillation dead time and capacitance C_T



Frequency (Hz)


Relationship between frequency and timing resistance

Off technology




The shutdown of UC2845 can be accomplished in two ways: by raising the No. 3 pin voltage above 1V or by lowering the No. 1 pin voltage to within the forward voltage drop of the two diodes at the ground level, both methods make the output of the PWM comparator high (see internal block diagram). The PWM latch trigger is preferentially reset so that the output is kept at a low level until the next clock cycle after the off signal of Pin 1 or Pin 3 is removed. An example of an external latch-off is achieved by adding a one-way SCR, which resets when the supply voltage VCC is below the UVLO threshold. At this point, the SCR is allowed to reset when the reference voltage is turned off.


Slope Compensation




A fraction of the oscillator ramp can be summed resistively with the current-sense signal to provide slope compensation for converters requiring duty cycles over 50%. Note that capacitor CCSF forms a filter with RCSF to suppress the leading-edge switch spikes.



Start current IST temperature characteristics



Temperature characteristics of power dissipation current ICC




Refer to the temperature characteristics of the voltage source Vref

Package Information




• DIP-8

Symbol	Size	Dimensions In Millimeters		Symbol	Size	Dimensions In Inches	
		Min(mm)	Max(mm)			Min(in)	Max(in)
A		3.710	4.310	A		0.146	0.170
A1		0.510		A1		0.020	
A2		3.200	3.600	A2		0.126	0.142
B		0.380	0.570	B		0.015	0.022
B1		1.524 (BSC)		B1		0.060 (BSC)	
C		0.204	0.360	C		0.008	0.014
D		9.000	9.400	D		0.354	0.370
E		6.200	6.600	E		0.244	0.260
E1		7.320	7.920	E1		0.288	0.312
e		2.540 (BSC)		e		0.100 (BSC)	
L		3.000	3.600	L		0.118	0.142
E2		8.400	9.000	E2		0.331	0.354



• SOP-8

Symbol	Dimensions In Millimeters		Symbol	Dimensions In Inches	
	Min (mm)	Max (mm)		Min (in)	Max (in)
A	1.350	1.750	A	0.053	0.069
A1	0.100	0.250	A1	0.004	0.010
A2	1.350	1.550	A2	0.053	0.061
b	0.330	0.510	b	0.013	0.020
c	0.170	0.250	c	0.006	0.010
D	4.700	5.100	D	0.185	0.200
E	3.800	4.000	E	0.150	0.157
E1	5.800	6.200	E1	0.228	0.224
e	1.270 (BSC)		e	0.050 (BSC)	
L	0.400	1.270	L	0.016	0.050
θ	0°	8°	θ	0°	8°



Statement:

- XBLW reserves the right to modify the product manual without prior notice! Before placing an order, customers need to confirm whether the obtained information is the latest version and verify the completeness of the relevant information.
- Any semi-guide product is subject to failure or malfunction under specified conditions. It is the buyer's responsibility to comply with safety standards when using XBLW products for system design and whole machine manufacturing. And take the appropriate safety measures to avoid the potential in the risk of loss of personal injury or loss of property situation!
- XBLW products have not been licensed for life support, military, and aerospace applications, and therefore XBLW is not responsible for any consequences arising from the use of this product in these areas.
- If any or all XBLW products (including technical data, services) described or contained in this document are subject to any applicable local export control laws and regulations, they may not be exported without an export license from the relevant authorities in accordance with such laws.
- The specifications of any and all XBLW products described or contained in this document specify the performance, characteristics, and functionality of said products in their standalone state, but do not guarantee the performance, characteristics, and functionality of said products installed in Customer's products or equipment. In order to verify symptoms and conditions that cannot be evaluated in a standalone device, the Customer should ultimately evaluate and test the device installed in the Customer's product device.
- XBLW documentation is only allowed to be copied without any alteration of the content and with the relevant authorization. XBLW assumes no responsibility or liability for altered documents.
- XBLW is committed to becoming the preferred semiconductor brand for customers, and XBLW will strive to provide customers with better performance and better quality products.