



**Part Number :** 982670538

**Series Number :** 98267

**Product Category :** Flexible Printed Circuit (FPC) Flex Jumpers

**Product Description :** 1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 102.00mm Cable Length, Tin (Sn) Plating, 36 Circuits

**Status :** Active

---

## Documents & Resources

### Drawings

Drawing 982670538\_sd.pdf

### Specifications

Product Specification PS-98267-001-001.pdf

---

## Product Environment Compliance

### Compliance

|                    |              |
|--------------------|--------------|
| China RoHS         | Not Reviewed |
| EU ELV             | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC         | Not Reviewed |
| EU RoHS            | Not Reviewed |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

---

## Part Details

General

|                |   |
|----------------|---|
| Status         | Active  |
| Category       | Flexible Printed Circuit (FPC) Flex Jumpers   |
| Series         | 98267   |
| Description    | 1.00mm Pitch Premo-Flex FFC Jumper, Opposite Side Contacts (Type D), 102.00mm Cable Length, Tin (Sn) Plating, 36 Circuits |
| Comments       | Contacts on opposite sides, Type D  |
| Product Family | FFC Cable Jumpers, Premo-Flex Flat-Flexible Cable Jumpers   |
| Product Name   | Premo-Flex FFC Jumper   |
| UPC            | 756054776230  |

Electrical

|                               |        |
|-------------------------------|--------|
| Current - Maximum per Contact | 1.2A   |
| Voltage - Maximum             | 60V AC |

Physical

|                               |                   |
|-------------------------------|-------------------|
| Cable Length                  | 102.00mm          |
| Circuits (Loaded)             | 36                |
| Contact Layout Type           | D (opposite side) |
| Design Feature                | Extra-Flexible    |
| Material - Plating Mating     | Tin               |
| Net Weight                    | 2.748/g           |
| Packaging Type                | Bag               |
| Pitch - Mating Interface      | 1.00mm            |
| Temperature Range - Operating | -40° to +105°C    |
| Termination Style             | FFC Connector     |
| Wire/Cable Type               | Flat Flex Cable   |
| Wire Size (AWG)               | N/A               |