


VS-P1223-P1223-C1020/ 1,0 - Cable



1609374

<https://www.phoenixcontact.com/us/products/1609374>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable, degree of protection: IP65, cable length: 1 m, number of positions: 5, material: PA-GF, PROFINET/power

Commercial data

Item number	1609374
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	ABNOIA
Catalog page	Page 352 (C-4-2015)
GTIN	4046356160957
Weight per piece (including packing)	344 g
Weight per piece (excluding packing)	215.251 g
Customs tariff number	85444290
Country of origin	DE

VS-P1223-P1223-C1020/ 1,0 - Cable



1609374

<https://www.phoenixcontact.com/us/products/1609374>

Technical data

Product properties

Product type	Data cable preassembled
Sensor type	PROFINET/power
Number of positions	5
Shielded	no

Electrical properties

Rated voltage (III/3)	400 V
Rated current	16 A (at 20 °C)
Nominal voltage U_N	400 V
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 100
-----------------------------	------------

Material specifications

Seal material O-ring	NBR
Seal material Cable seal	TPE
Housing material	PA-GF
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	PA
Outer sheath, material	PVC
Conductor material	Bare Cu litz wires

Connector

Connection 1

Type	Plug straight MSTB
Locking type	Push Pull
Degree of protection	IP65

Connection 2

Type	Plug straight MSTB
Locking type	Push Pull
Degree of protection	IP65

Cable/line

Cable length	1.00 m
--------------	--------

PVC gray [PVC]

Cable weight	242 kg/km
--------------	-----------

VS-P1223-P1223-C1020/ 1,0 - Cable



1609374

<https://www.phoenixcontact.com/us/products/1609374>

Number of positions	5
Shielded	no
Cable type	PVC gray [PVC]
Conductor cross section	5x 2.5 mm²
External cable diameter	11.80 mm
Outer sheath, material	PVC
External sheath, color	gray RAL 7001
Conductor material	Bare Cu litz wires
Material wire insulation	PVC
Single wire, color	blue, brown, black, gray, green/yellow
Overall twist	5 cores, twisted
Insulation resistance	> 0.2 MΩ*km
Nominal voltage, cable	750 V
	1000 V (Fixed, protected installation)
Test voltage	4000 V
Minimum bending radius, fixed installation	4 x D
Minimum bending radius, flexible installation	15 x D
Smallest bending radius, fixed installation	48 mm
Smallest bending radius, movable installation	177 mm
Flame resistance	according to IEC 60332-1-2
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
	-5 °C ... 70 °C (Cable, flexible installation)


Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65
	IP67
	IP65
Ambient temperature (operation)	-40 °C ... 70 °C (cable, fixed installation)
	-5 °C ... 70 °C (Cable, flexible installation)
	-40 °C ... 70 °C (Plug / socket)


Drawings

Schematic diagram



Connector pin assignment for PROFINET Push-Pull, power connector, 400 V

Dimensional drawing



Push-Pull MSTB connector IP65/67

VS-P1223-P1223-C1020/ 1,0 - Cable



1609374
<https://www.phoenixcontact.com/us/products/1609374>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com