

#### zQSFP+/QSFP28

TE Internal #: 2308171-1

zQSFP+, Cage Assembly with Integrated Connector, .8mm [.032in]

Centerline, Signal, Operating Temperature Range -40 – 85 °C [-40 –

185 °F]

View on TE.com >



Connectors > Pluggable IO Connectors & Cages











Pluggable I/O Product Type: Cage Assembly with Integrated Connector

Centerline (Pitch): .8 mm [ .032 in ]

Sealable: No

Circuit Application: Signal

Operating Temperature Range: -40 - 85 °C [-40 - 185 °F]

### Features

#### **Product Type Features**

| Cage Type                  | Stacked                                 |
|----------------------------|---|
| Pluggable I/O Product Type | Cage Assembly with Integrated Connector |
| Sealable                   | No                                      |
| Form Factor                | zQSFP+                                  |

### **Configuration Features**

| Number of Rear EONs per Port Column | 0     |
|-------------------------------------|-------|
| Number of Positions                 | 152   |
| Number of Ports                     | 4     |
| Port Matrix Configuration           | 2 x 2 |

#### **Contact Features**

| Contact Mating Area Plating Material Thickness | 30 μm[.76 μin] |
|--|----------------|
| Contact Mating Area Plating Material           | Gold           |
| PCB Contact Termination Area Plating Material  | Tin            |
| Contact Current Rating (Max)                   | .5 A           |



#### **Termination Features**

| Termination Post & Tail Length | 2 mm[.079 in]            |
|--------------------------------|--------------------------|
| Termination Method to PCB      | Through Hole - Press-Fit |
| Housing Features               |                          |

Nickel Silver Alloy

.8 mm[.032 in]

# Dimensions

Cage Material

Centerline (Pitch)

| PCB Thickness (Recommended) | 3 mm[.118 in] |
|-----------------------------|---------------|

# **Usage Conditions**

| Operating Temperature Range | -40 - 85 °C[-40 - 185 °F] |
|-----------------------------|---------------------------|

# Operation/Application

| Pluggable I/O Applications | QSFP28 |
|----------------------------|--------|
| Heat Sink Compatible       | No     |
| Circuit Application        | Signal |

### **Industry Standards**

| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|
|------------------------|----------|

# **Packaging Features**

| Packaging Method | Box & Tray |  |
|------------------|------------|--|
|------------------|------------|--|

#### Other

| Included Lightpipe           | Yes                           |
|------------------------------|-------------------------------|
| EMI Containment Feature Type | Internal/External EMI Springs |

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900   |



ppm.

#### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**





# Also in the Series | zQSFP+/QSFP28







Pluggable I/O Cable Assemblies(78)



Pluggable IO Connectors & Cages(424)

# Customers Also Bought







TE Part #1-2325185-1
RCPT CAGE ASSY W/ L-HS &2LP 1X2
QSFP-DD

zQSFP+, Cage Assembly with Integrated Connector, .8mm [.032in] Centerline, Signal, Operating Temperature Range -40 – 85 °C [-40 – 185 °F]



TE Part #1-2325185-3

RCPT CAGE ASSY W/ L-HS &2LP 1X2

QSFP-DD

TE Part #2-2214617-5
SFP+assy 2x1 EMI Spring, 4LP Sn



TE Part #2334543-3 MBPULS,BOARD SIDE

TE Part #3-2007637-5 SFP+ 2x2, SPR, 4 LP Enhanced, HF, NI

### **Documents**

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_2308171-1\_A1.3d\_igs.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2308171-1\_A1.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2308171-1\_A1.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Product Specifications**

**Application Specification** 

English