



Part Number : [1724580212](#)

Product Description : EXTreme Ten60Power Panel-to-Board Right-Angle Plug Assembly with Guide Pins, 1 Power Circuit, 12 Signal Circuits, 1 Power Circuit

Series Number : 172458

Status : Active

Product Category : PCB Headers and Receptacles



Documents & Resources

Drawings

[1724580212_sd.pdf](#)

[PK-46437-003-001.pdf](#)

3D Models and Design Files

[1724580212_stp.zip](#)

[SYM-172458-0212-001.zip](#)

Specifications

[1724520000-AS-000.pdf](#)

[PS-173693-001-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 34; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	PCB Headers and Receptacles
Series	172458
Description	EXTreme Ten60Power Panel-to-Board Right-Angle Plug Assembly with Guide Pins, 1 Power Circuit, 12 Signal Circuits, 1 Power Circuit
Application	Panel-to-Board, Power, Signal
Component Type	PCB Header
Keyword	Ten60
Product Name	EXTreme Ten60Power
UPC	889056069601

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	50.0A
Voltage - Maximum	600V AC / 250V DC

Physical

Breakaway	No
Circuits (Loaded)	14
Circuits (maximum)	14
Color - Resin	Black
Durability (mating cycles max)	200

First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Side, Yes
Keying to Mating Part	None
Lock to Mating Part	No
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	Liquid Crystal Polymer
Net Weight	11.738/g
Number of Rows	1, 3
Orientation	Right Angle
Packaging Type	Tray
PC Tail Length	2.84mm
PCB Retention	Yes
Pitch - Mating Interface	2.54mm
Plating min - Mating	0.762µm
Plating min - Termination	2.540µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
(p)ower-(s)ignal Configuration	1p - 12s - 1p
Shrouded	No
Stackable	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole

Mates With / Use With

Mates with Part(s)

Description	Part Number
EXTreme Ten60Power Panel-to-Board Receptacle Housings	<u>172512</u>

This document was generated on Nov 01, 2024