

Search within category

GO

BUY NOW

DESIGN / INSTALL



BT1.5I-M300

Dome-Top® barb ty cable tie, intermediate cross section, 6.1" (155mm) length, heat stabilized weather resistant nylon 6.6, black.

Specs	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Std. Pkg. Qty.	1000			
Material	Heat Stabilized Weather Resistant Nylon 6.6			
Color	Black			
Cross Section	Intermediate			
Length (In.)	6.1			
Length (mm)	155			
Locking Style	Locking			
Width (In.)	0.141			
Width (mm)	3.6			
Min. Loop Tensile Strength Lbs. (N)	40 (178)			
Continuous Use Temperature Range	-76° (-60°) - 185° (85°)			
Plenum-Rated	No			
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2			
Length In (mm)	6.10 (155)			
Thickness In (mm)	0.04 (1.0)			
Bundle Diameter Range In. (mm)	0.03 (0.8) - 1.50 (38)			
CE Compliant	Yes			
CSA Certified	Yes			
Mil. Std. Part Number	—			
UL 62275 Compliant (Type 2, 21)	Yes			
UL Listed (File #E56854)	Yes			
UL Recognized (File #E56854)	No			
Application	General			
Environment	Outdoor (UV Resistant)			
Max. Bundle Diameter (In.)	1.50			
Max. Bundle Diameter (mm)	38			



Max. Continuous Use Temperature 212°F (100°C)

Min. Bundle Diameter (In.) 0.06

[LEGAL INFORMATION](#) | [PRIVACY POLICY](#) | [CONTACT US](#) | [SITE MAP](#) | [WHERE TO BUY](#) | [JOBS](#)

Min. Bundle Diameter (mm) 1.5

Min. Loop Tensile Strength (Lbs.) 40

Min. Loop Tensile Strength (N) 178

Product Type Cable Ties

Thickness (In.) 0.041

Thickness (mm) 1.0

Width In (mm) 0.14 (3.6)

RoHS Compliancy Status Compliant

Min. Order Qty. 1,000.0000