



Part Number : [734035114](#)
Product Description : 50 Ohms, FAKRA SMB Jack, Right-Angle, Through Hole, Brass Body, Keying Option E, Green
Series Number : 73403
Status : Active
Product Category : RF / Coaxial Connectors



Documents & Resources

Drawings

[Drawing 734035114_sd.pdf](#)

3D Models and Design Files


[3D Model 734035114_stp.zip](#)

Specifications

[Product Specification PS-89675-331-001.pdf](#)

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|--|
| Status | Active |
| Category | RF / Coaxial Connectors |
| Series | 73403 |
| Description | 50 Ohms, FAKRA SMB Jack, Right-Angle, Through Hole, Brass Body, Keying Option E, Green |
| Application | Automotive |
| Product Family | FAKRA PCB, Cable and Sealed Connection Systems |
| Product Name | FAKRA,SMB |
| Style | PCB |
| Type | Subminiature |
| UPC | 883906687656 |

Electrical

| | |
|-----------------|-----------------------------|
| Frequency | 6 GHz |
| Impedance | 50Ω |
| Power / Voltage | VOLTAGE: 335 Vrms@Sea Level |

Physical

| | |
|-----------------------|--------------|
| Gender | Jack |
| Keying to Mating Part | Yes |
| Net Weight | 4.441/g |
| Orientation | Right Angle |
| Packaging Type | Tray |
| Panel Mount | No |
| Panel Mount Method | N/A |
| PCB Mounting | Through Hole |
| Reverse Polar | No |
| Wire/Cable Type | N/A |

Solder Process Data

| | |
|------------------------------|----------|
| Max-Duration | 10 |
| Lead-Free Process Capability | SMC&WAVE |
| Max-Cycle | 2 |
| Max-Temp | 260 |

This document was generated on Sep 18, 2024