


Connectors for Automobiles

Connect with the Best

[How to choose connectors](#)
[Notes on usage](#)
[User Guide](#)
[Catalogue PDF](#)

results

Product information



[Contact us for products](#)

8100-0468

[TS sealed series](#)
[HX sealed series](#)
[DL sealed series](#)

Terminal For AV Wire


4.8mm(187)

Sealed/Unsealed	sealed
Male/Female	F
Tab Size	4.8mm(187)
Size	L
Mating parts	8100-0465 (TS sealed series/HX sealed series/DL sealed series)
Applicable wire size	2.0-3.0mm ²
Materials	Heat-resistant copper alloy
Surface treatment	Tin-plated
Contact resistance	Initial 3mΩ Max. after durability tests 10mΩ Max.
Leak current	100μA Max.
Insulation resistance	100MΩ Min.

Note This part is applicable to use for both new type and old type.

TS sealed series 4.8mm(187) related products

► Housing (30)




[0.64/2.3/4.8mm 6189-7094](#)



[0.64/2.3/4.8mm 6189-7809](#)




[0.64/4.8mm 6189-1048](#)



[0.64/4.8mm 6189-7426](#)

[Show all results](#)

► Wire seals (4)



[4.8mm 7165-0346](#)



[4.8mm 7165-0347](#)



[4.8mm 7165-0356](#)



[4.8mm 7165-0348](#)

HX sealed series 4.8mm(187) related products

► Housing (4)



1.0/4.8mm 6189-6863



1.5/4.8mm 6189-7411




1.5/4.8mm 6189-7567




2.3/4.8mm 6189-0555


► Wire seals (5)




4.8mm 7165-0172



4.8mm 7165-0130



4.8mm 7165-0147




4.8mm 7165-0131


Show all results

DL sealed series 4.8mm(187) related products


► Housing (5)




1.0/4.8mm 6189-6968



1.0/4.8mm 6189-6967



2.3/4.8mm 6195-0069



2.3/4.8mm 6195-0170

Show all results

► Wire seals (4)



4.8mm 7165-0346



4.8mm 7165-0347



4.8mm 7165-0356



4.8mm 7165-0348