


# USB3 A to Micro-B Active Optical Cables

10m/15m/20m/30m/40m/50m/60m/70m/80m/90m/100m

- **support High Speed & High Resolution USB3 Cameras**  
high frame rate 170 fps at full 2.0~2.3 MP resolution,  
high frame rate 90 fps at full 4.0~4.2 MP resolution  
(430 MB/s wide bandwidth data throughput)  
**without lost frames all the time.**
- **USB 2.0/1.1/1.0 not supported**



CBL-U3AOC03-10m



CBL-U3AOC03-15m



CBL-U3AOC03-20m



CBL-U3AOC03-30m



# **Ultra Slim** **USB3 Straight A to Straight Micro-B Machine Vision Camera Cables - M/M** with locking screws on Micro-B plug [ 1m,2m,3m,4m,5m,6m,7m,8m,9m,10m,...,20m ] O.D. : 4.3mm, 30AWG - U3 / 32AWG - U2 / 24AWG-PWR



- support High Speed & High Resolution USB3 Cameras  
 high frame rate 170 fps at full 2.0~2.3 MP resolution, high frame rate 90 fps at full 4.0~4.2 MP resolution  
 (430 MB/s wide bandwidth data throughput)  
 without lost frames all the time.

## **Flexible** Wide Bandwidth




| USB A(M) | PIN OUT    | USB MicroB(M) |
|----------|------------|---------------|
| 1        | RED        | 1             |
| 2        | WHITE      | 2             |
| 3        | GREEN      | 3             |
| 4        | BLACK      | 5             |
| 5        | BLUE       | 6             |
| 6        | YELLOW     | 7             |
| 7        | DRAIN WIRE | 8             |
| 8        | PURPLE     | 9             |
| 9        | ORANGE     | 10            |
| SHELL    | BRAID      | SHELL         |


[ 1m,2m,3m ]

CBL-USPD302MBSWB-1m/2m/3m (Passive Type-no repeater)

• Straight USB 3.0 A Plug :



• Straight USB 3.0 Micro-B Plug :



## **Flexible** Wide Bandwidth




| USB A(M) | PIN OUT    | USB MicroB(M) |
|----------|------------|---------------|
| 1        | RED        | 1             |
| 2        | WHITE      | 2             |
| 3        | GREEN      | 3             |
| 4        | BLACK      | 5             |
| 5        | BLUE       | 6             |
| 6        | YELLOW     | 7             |
| 7        | DRAIN WIRE | 8             |
| 8        | PURPLE     | 9             |
| 9        | ORANGE     | 10            |
| SHELL    | BRAID      | SHELL         |

[ 4m,5m,6m,7m,8m ]

CBL-USD302MBSWB-4m/5m/6m/7m/8m (Active Type-with 1 repeater)

• Straight USB 3.0 A Plug :



• Straight USB 3.0 Micro-B Plug :








## [ 9m,10m,11m,12m ]

CBL-USD302MBSS-9m/10m/11m/12m (Active Type-with 2 repeaters)




• Straight USB 3.0 A Plug :



## [ 13m,14m,15m,16m ]

CBL-USD302MBSS-13m/14m/15m/16m (Active Type-with 3 repeaters)




• Straight USB 3.0 A Plug :



## [ 17m,18m,19m,20m ]

CBL-USD302MBSS-17m/18m/19m/20m (Active Type-with 4 repeaters)

• Straight USB 3.0 A Plug :



• fit for Basler's small cameras



• fit for IDS's small cameras



• fit for JAI's small cameras



• fit for Matrix Vision's small cameras



• fit for Point Grey's small cameras



• fit for SENTECH's small cameras



• fit for SVS-VISTEK's small cameras



• fit for The Imaging Source's small cameras



• fit for Toshiba Teli's small cameras



• fit for XIMEA's small cameras



Left Angle



Right Angle



Up Angle



Down Angle



Passive  
Compact

## USB3 Straight A to Micro-B Machine Vision Camera Cables - M/M

with locking screws on Micro-B plug

[ 1m,2m,3m,4m,5m,6m,7m ]

O.D. : 5.6mm, 28AWG - U3 / 28AWG - U2 / 20AWG-PWR



### • support High Speed & High Resolution USB3 Cameras

high frame rate 170 fps at full 2.0~2.3 MP resolution, high frame rate 90 fps at full 4.0~4.2 MP resolution  
(500 MB/s wide bandwidth data throughput)  
without lost frames all the time.



• fit for Basler's small cameras



• fit for IDS's small cameras



• fit for JAI's small cameras



• fit for Matrix Vision's small cameras



• fit for Point Grey's small cameras



• fit for SENTECH's small cameras



• fit for SVS-VISTEK's small cameras



• fit for The Imaging Source's small cameras



• fit for Toshiba Teli's small cameras



• fit for XIMEA's small cameras

### Wide Bandwidth




| USB A(M) |            | USB MicroB(M) |
|----------|------------|---------------|
| 1        | RED        | 1             |
| 2        | WHITE      | 2             |
| 3        | GREEN      | 3             |
| 4        | BLACK      | 5             |
| 5        | BLUE       | 6             |
| 6        | YELLOW     | 7             |
| 7        | DRAIN WIRE | 8             |
| 8        | PURPLE     | 9             |
| 9        | ORANGE     | 10            |
| SHELL    | BRAND      | SHELL         |

[ 1m,2m,3m,4m,5m,6m,7m ]


CBL-PD302MBS-1m/2m/3m

CBL-PD302MBSWB-4m/5m/6m/7m

• Straight USB 3.0 A Plug :



• Straight USB 3.0 Micro-B Plug :





### Wide Bandwidth



Left Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | BRAID         |
|              | SHELL         |

[ 1m,2m,3m,4m,5m,6m,7m ]

CBL-PD302MBS-1mLA/2mLA/3mLA

CBL-PD302MBSWB-4mLA/5mLA/6mLA/7mLA



### Wide Bandwidth




Right Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | BRAID         |
|              | SHELL         |

[ 1m,2m,3m,4m,5m,6m,7m ]

CBL-PD302MBS-1mRA/2mRA/3mRA

CBL-PD302MBSWB-4mRA/5mRA/6mRA/7mRA



### Wide Bandwidth



Up Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | BRAID         |
|              | SHELL         |

[ 1m,2m,3m,4m,5m,6m,7m ]

CBL-PD302MBS-1mUA/2mUA/3mUA

CBL-PD302MBSWB-4mUA/5mUA/6mUA/7mUA



### Wide Bandwidth



Down Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | BRAID         |
|              | SHELL         |

[ 1m,2m,3m,4m,5m,6m,7m ]

CBL-PD302MBS-1mDA/2mDA/3mDA

CBL-PD302MBSWB-4mDA/5mDA/6mDA/7mDA





Active


Compact

## USB3 Straight A to Micro-B Machine Vision Camera Cables - M/M

with locking screws on Micro-B plug

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]

O.D. : 5.6mm, 28AWG - U3 / 28AWG - U2 / 20AWG-PWR



### • support High Speed & High Resolution USB3 Cameras

high frame rate 170 fps at full 2.0~2.3 MP resolution, high frame rate 90 fps at full 4.0~4.2 MP resolution  
(500 MB/s wide bandwidth data throughput)  
without lost frames all the time.



• fit for Basler's small cameras



• fit for IDS's small cameras



• fit for JAI's small cameras



• fit for Matrix Vision's small cameras



• fit for Point Grey's small cameras



• fit for SENTECH's small cameras



• fit for SVS-VISTEK's small cameras



• fit for The Imaging Source's small cameras



• fit for Toshiba Teli's small cameras



• fit for XIMEA's small cameras

### Wide Bandwidth




| PIN OUT  |            |               |
|----------|------------|---------------|
| USB A(M) |            | USB MicroB(M) |
| 1        | RED        | 1             |
| 2        | WHITE      | 2             |
| 3        | GREEN      | 3             |
| 4        | BLACK      | 5             |
| 5        | BLUE       | 6             |
| 6        | YELLOW     | 7             |
| 7        | DRAIN WIRE | 8             |
| 8        | PURPLE     | 9             |
| 9        | ORANGE     | 10            |
| SHELL    | BRAID      | SHELL         |

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]


CBL-ED302MBCS-5m/7m/10m

CBL-ED302MBCSWB-15m/20m/25m/30m/35m/40m/45m/50m

• Straight USB 3.0 A Plug :



• Straight USB 3.0 Micro-B Plug :





### Wide Bandwidth




Left Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | SHELL         |
|              | BRAID         |

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]

CBL-ED302MBCS-5mLA/7mLA/10mLA

CBL-ED302MBCSWB-15mLA/20mLA/25mLA/  
30mLA/35mLA/40mLA/45mLA/50mLA



### Wide Bandwidth




Right Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | SHELL         |
|              | BRAID         |

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]

CBL-ED302MBCS-5mRA/7mRA/10mRA

CBL-ED302MBCSWB-15mRA/20mRA/25mRA/  
30mRA/35mRA/40mRA/45mRA/50mRA



### Wide Bandwidth




Up Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | SHELL         |
|              | BRAID         |

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]

CBL-ED302MBCS-5mUA/7mUA/10mUA

CBL-ED302MBCSWB-15mUA/20mUA/25mUA/  
30mUA/35mUA/40mUA/45mUA/50mUA



### Wide Bandwidth




Down Angle

| PIN OUT      |               |
|--------------|---------------|
| USB A(M)     | USB MicroB(M) |
| 1 RED        | 1             |
| 2 WHITE      | 2             |
| 3 GREEN      | 3             |
| 4 BLACK      | 5             |
| 5 BLUE       | 6             |
| 6 YELLOW     | 7             |
| 7 DRAIN WIRE | 8             |
| 8 PURPLE     | 9             |
| 9 ORANGE     | 10            |
| SHELL        | SHELL         |
|              | BRAID         |

[ 5m, 7m, 10m, 15m, 20m, 25m, 30m, 35m, 40m, 45m, 50m ]

CBL-ED302MBCS-5mDA/7mDA/10mDA

CBL-ED302MBCSWB-15mDA/20mDA/25mDA/  
30mDA/35mDA/40mDA/45mDA/50mDA



### Repeater(s):

5m:1 / 7m:1 / 10m:1 / 15m:2 / 20m:3 / 25m:4 / 30m:4 / 35m:6 / 40m:7 / 45m:8 / 50m:8



# High-Flex (Continuous-Flex)

- Flex Testing:
  - (1) TYPE-U (Rolling, C-Track, C-Chain) / R=67.5mm ► Minimum 5,000,000 times
  - (2) TYPE-S / R=60mm ► Minimum 1,000,000 times
  - (3) 90° BENDING (Tick-Tock Bending) / R=60mm ► Minimum 1,000,000 times
- Cable O.D.: 5.4mm


## Passive USB2 Connectors & Cable Assemblies for Automated Systems

- 1m/2m/3m/4m/5m/6m/7m/8m/9m/10m




CBL-HFPD203MBS-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 mini-B Plug :




CBL-HFPD203MB-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 mini-B Plug :




CBL-HFPD203-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :



• Straight USB 2.0 B Plug :






# High-Flex (Continuous-Flex)


- Flex Testing:
  - (1) TYPE-U (Rolling, C-Track, C-Chain) / R=67.5mm ▶ Minimum 5,000,000 times
  - (2) TYPE-S / R=60mm ▶ Minimum 1,000,000 times
  - (3) 90° BENDING (Tick-Tock Bending) / R=60mm ▶ Minimum 1,000,000 times
- Cable O.D.: 5.4mm

## Active USB2 Connectors, Repeater(s) & Cable Assemblies for Automated Systems - 15m/20m/25m/30m/35m/40m/50m




CBL-HFD203MBS-15m/20m/25m/30m/35m/40m/45m/50m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 mini-B Plug :




CBL-HFD203MB-15m/20m/25m/30m/35m/40m/45m/50m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 mini-B Plug :




CBL-HFD203-15m/20m/25m/30m/35m/40m/45m/50m

• Straight USB 2.0 A Plug :



• Straight USB 2.0 B Plug :






# High-Flex (Continuous-Flex)

- Flex Testing:
  - (1) TYPE-U (Rolling, C-Track, C-Chain) / R=87mm ▶ Minimum 5,000,000 times
  - (2) TYPE-S / R=60mm ▶ Minimum 1,000,000 times
  - (3) 90° BENDING (Tick-Tock Bending) / R=60mm ▶ Minimum 1,000,000 times
- support High Speed & High Resolution USB3 Cameras
 


high frame rate 170 fps at full 2.0~2.3 MP resolution, high frame rate 90 fps at full 4.0~4.2 MP resolution (430 MB/s wide bandwidth data throughput)

**without lost frames all the time.**
- USB 2.0/1.1/1.0 not supported
- Cable O.D.:5.6mm

## Passive USB3 Connectors & Cable Assemblies for Automated Systems - 1m/2m/3m




## Active USB3 Connectors, Repeater(s) & Cable Assemblies for Automated Systems - 4m/5m/6m/7m/8m/9m/10m/...../20m






# Passive USB2 Machine Vision Camera Cables

- 1m/2m/3m/4m/5m/6m/7m/8m/9m/10m




CBL-PD203MBS-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :



• Straight USB 2.0 mini-B Plug :




CBL-PD203MB-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 mini-B Plug :




CBL-PD203-1m/2m/3m/4m/5m/6m/7m/8m/9m/10m

• Straight USB 2.0 A Plug :




• Straight USB 2.0 B Plug :





# Long Distance **Active USB2** Machine Vision Camera Cables



USB 2.0 industrial camera


USB 2.0 Mini-B 5-pin plug, with locking screws (threaded M2)



CBL-D203MBS-5m/7m/10m/15m/20m/25m/30m/35m/40m/45m/50m/55m/60m/65m/70m/75m/80m

• Straight USB 2.0 A Plug :


• Straight USB 2.0 mini-B Plug :



**Connects a USB 2.0 camera located**

5/7/10/15/20/25/30/35/40/45/50/55/60/65/70/80 meters

(16/22/32/49/65/82/98/114/131/147/164/180/196/213/262 feet) far away!!



USB 2.0 industrial camera


USB 2.0 Mini-B 5-pin plug



CBL-D203MB-5m/7m/10m/15m/20m/25m/30m/35m/40m/45m/50m/55m/60m/65m/70m/75m/80m

• Straight USB 2.0 A Plug :


• Straight USB 2.0 mini-B Plug :



**Connects a USB 2.0 device located**

5/7/10/15/20/25/30/35/40/45/50/55/60/65/70/80 meters

(16/22/32/49/65/82/98/114/131/147/164/180/196/213/262 feet) far away!!



USB 2.0 industrial camera


USB 2.0 B plug



CBL-D203-5m/7m/10m/15m/20m/25m/30m/35m/40m/45m/50m/55m/60m/65m/70m/75m/80m

• Straight USB 2.0 A Plug :

• Straight USB 2.0 B Plug :



**Connects a USB 2.0 device located**

5/7/10/15/20/25/30/35/40/45/50/55/60/65/70/80 meters

(16/22/32/49/65/82/98/114/131/147/164/180/196/213/262 feet) far away!!