

## STRATO-THERM

TE Internal #: 1577633-1


Closed Ring Tongue Terminal, 18 – 16 AWG, #10 Stud Size, 5 mm [. 197 in] Stud Diameter, Closed Barrel, Straight, Nickel, STRATO-

THERM

View on TE.com >



Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 1600 – 2800 CMA

Stud Size: #10

## **Features**

## **Product Type Features**

Troduct Type reduces	
Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#10
Sealable	No
Wire Insulation Support Retention Type	Non-Insulation Support
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Nickel
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	1600 – 2800 CMA
Stud Diameter	5 mm[.197 in]
Tongue Thickness	.79 mm[.031 in]
Product Length	22.43 mm[.883 in]



Compatible Insulation Diameter (Max)	2.67 mm[.106 in]
Compatible Insulation Diameter Range	1.4 – 2.67 mm[.055 – .106 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	260 °C[500 °F]
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag/Box

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts


















## Also in the Series | STRATO-THERM







# Customers Also Bought



SOCKET CONTACT SIZE 12 GPR



TE Part #1577648-1 TERMINAL RT PIDG PEEK STRATO 10 AWG



TE Part #1577632-1 TERMINAL RT PIDG PEEK STRATO 18-16 AWG



TE Part #1577646-1 TERMINAL RT PIDG PEEK STRATO 10 **AWG** 



FDBA 56-20-41 PN-K 090



TE Part #1394278-1 KIT, BACKSHELL, AMPLIMITE, HD, 50

TE Part #1-2386957-1 86A3-08-1-G-CP1-CV4042



TE Part #679953-000
B-013-10CS2689

TE Part #200980-000
B-013-11CS2689

## **Documents**

## **Product Drawings**

**TERMINAL RT PIDG PEEK STRATO 18-16 AWG** 

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1577633-1\_B.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1577633-1\_B.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1577633-1\_B.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## **Product Specifications**

**Application Specification** 

English