

1424834

<https://www.phoenixcontact.com/us/products/1424834>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sleeve housing B32, for double locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, lateral, 1x Pg36, height: 94 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1424834
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 644 (C-2-2019)
GTIN	4055626382395
Weight per piece (including packing)	424.7 g
Weight per piece (excluding packing)	424 g
Customs tariff number	85389099
Country of origin	CN

HC-STA-B32-HHFD-1STP36-EL-AL - Housing



1424834


<https://www.phoenixcontact.com/us/products/1424834>

Technical data

Product properties

Product type	Housing with locking latch
Housing type	Sleeve housing
Application	Standard
Type	B32
No. of cable outlets	1
Type of the screw connection	1x Pg36
Type	Tall design
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	82.5 mm
Height	94 mm
Length	94 mm

Material specifications

Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated

Mechanical properties

Mechanical data

Type of the screw connection	1x Pg36
Locking type	Pin

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
	IP67
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

HC-STA-B32-HHFD-1STP36-EL-AL - Housing


1424834

<https://www.phoenixcontact.com/us/products/1424834>



Drawings

Dimensional drawing



Dimensional drawing

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424834>

**DNV**
Approval ID: TAE000037S

**cUL Recognized**
Approval ID: E255026

**UL Recognized**
Approval ID: E255026

**EAC**
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

HC-STA-B32-HHFD-1STP36-EL-AL - Housing



1424834

<https://www.phoenixcontact.com/us/products/1424834>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-STA-B32-HHFD-1STP36-EL-AL - Housing



1424834

<https://www.phoenixcontact.com/us/products/1424834>

Accessories

HC-B32-HCWD-PLR-BK - Protective cover

1346555

<https://www.phoenixcontact.com/us/products/1346555>

Protective cover B32, with double locking latch, protective cover material: PC, height: 26.4 mm, seal: yes



US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/us/products/0830085>

Plastic label, Card, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



HC-STA-B32-HHFD-1STP36-EL-AL - Housing

1424834

<https://www.phoenixcontact.com/us/products/1424834>



US-EMLP-HA (20X9) - Plastic label

0830989

<https://www.phoenixcontact.com/us/products/0830989>



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 PG36 BK - Screw connection

3240894

<https://www.phoenixcontact.com/us/products/3240894>



Cable gland, Pg thread, IP66 protection, straight

HC-STA-B32-HHFD-1STP36-EL-AL - Housing

1424834

<https://www.phoenixcontact.com/us/products/1424834>



WP-G HF IP69K PG36 BK - Screw connection

3240880

<https://www.phoenixcontact.com/us/products/3240880>



Cable gland, Pg thread, IP68/69k protection, straight

WP-G PP HF PG21 - Screw connection

3240992

<https://www.phoenixcontact.com/us/products/3240992>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B32-HHFD-1STP36-EL-AL - Housing

1424834

<https://www.phoenixcontact.com/us/products/1424834>



WP-GA HF IP69K PG36 BK - Screw connection

3240908

<https://www.phoenixcontact.com/us/products/3240908>

Cable gland, Pg thread, IP68/69k protection, angled



WP-GR HF IP66 PG36 BK - Screw connection

3240950

<https://www.phoenixcontact.com/us/products/3240950>

Cable gland, Pg thread, IP66 protection, with strain relief



HC-STA-B32-HHFD-1STP36-EL-AL - Housing

1424834

<https://www.phoenixcontact.com/us/products/1424834>



WP-GR HF IP69K PG36 BK - Screw connection

3240936

<https://www.phoenixcontact.com/us/products/3240936>



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG36 - Screw connection

3240994

<https://www.phoenixcontact.com/us/products/3240994>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B32-HHFD-1STP36-EL-AL - Housing



1424834

<https://www.phoenixcontact.com/us/products/1424834>

WP-GT PP HF PG36 - Screw connection

3241008

<https://www.phoenixcontact.com/us/products/3241008>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG36 - Screw connection

3241043

<https://www.phoenixcontact.com/us/products/3241043>



Cable gland made from brass with Pg thread, IP40 protection

HC-STA-B32-HHFD-1STP36-EL-AL - Housing



1424834

<https://www.phoenixcontact.com/us/products/1424834>

WP-GT BRASS PG36 - Screw connection

3241029

<https://www.phoenixcontact.com/us/products/3241029>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



WP-G BRASS IP65 PG36 - Screw connection

3241057

<https://www.phoenixcontact.com/us/products/3241057>

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com