


KMM Series

- Longer life from KMQ series
- Endurance with ripple current : 2,000 to 3,000 hours at 105°C
- Non solvent resistant type
- RoHS2 Compliant




SPECIFICATIONS

Items	Characteristics			
Category	-25 to +105℃			
Temperature Range				
Rated Voltage Range	160 to 450V _{dc}			
Capacitance Tolerance	± 20% (M) (at 20℃, 120Hz)			
Leakage Current	I ≤ 3/CV Where, I : Max. leakage current (μA), C : Nominal capacitance (μF), V : Rated voltage (V) (at 20℃ after 5 minutes)			
Dissipation Factor (tan δ)	Rated voltage (V _{ac})	160 to 400V	420 & 450V	(at 20℃, 120Hz)
	tan δ (Max.)	0.15	0.20	
Low Temperature Characteristics (Max. Impedance Ratio)	Rated voltage (V _{ac})	160 to 400V	420 & 450V	(at 120Hz)
	Z(-25℃)/Z(+20℃)	4	8	
Endurance	The following specifications shall be satisfied when the capacitors are restored to 20℃ after subjected to DC voltage with the rated ripple current is applied (the peak voltage shall not exceed the rated voltage)for 3,000 hours at 105℃.			
	Capacitance change	≤ ±20% of the initial value		
	D.F. (tan δ)	≤200% of the initial specified value		
	Leakage current	≤The initial specified value		
Shelf Life	The following specifications shall be satisfied when the capacitors are restored to 20℃ after exposing them for 1,000 hours at 105℃ without voltage applied. Before the measurement, the capacitor shall be preconditioned by applying voltage according to Item 4.1 of JIS C 5101-4.			
	Capacitance change	≤ ± 15% of the initial value		
	D.F. (tan δ)	≤ 150% of the initial specified value		
	Leakage current	≤The initial specified value		

DIMENSIONS [mm]


- Terminal Code : VS (φ22 to φ35) : Standard




*φD=35mm : 3.5±0.5mm

The standard design has no plastic disc.

- Terminal Code : LI (φ35)



PART NUMBERING SYSTEM



Please refer to "Product code guide (snap-in type)"

◆ **STANDARD RATINGS**

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.	WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.
160	220	22 × 20	0.15	0.81	EKMM161VSN221MP20S	180	1,200	25.4 × 50	0.15	2.55	EKMM181VSN122MQ50S
	270	25.4 × 20	0.15	0.98	EKMM161VSN271MQ20S		1,200	30 × 40	0.15	2.55	EKMM181VSN122MR40S
	330	22 × 25	0.15	1.20	EKMM161VSN331MP25S		1,200	35 × 30	0.15	2.55	EKMM181VSN122MA30S
	330	25.4 × 20	0.15	1.02	EKMM161VSN331MQ20S		1,500	30 × 45	0.15	2.90	EKMM181VSN152MR45S
	390	22 × 25	0.15	1.30	EKMM161VSN391MP25S		1,500	35 × 35	0.15	2.90	EKMM181VSN152MA35S
	390	25.4 × 25	0.15	1.26	EKMM161VSN391MQ25S		1,800	30 × 60	0.15	3.49	EKMM181VSN182MR60S
	390	30 × 20	0.15	1.25	EKMM161VSN391MR20S		1,800	35 × 40	0.15	3.30	EKMM181VSN182MA40S
	470	22 × 30	0.15	1.55	EKMM161VSN471MP30S		2,200	35 × 50	0.15	3.65	EKMM181VSN222MA50S
	470	25.4 × 25	0.15	1.55	EKMM161VSN471MQ25S		2,700	35 × 60	0.15	4.19	EKMM181VSN272MA60S
	470	30 × 20	0.15	1.30	EKMM161VSN471MR20S	200	150	22 × 20	0.15	0.73	EKMM201VSN151MP20S
	560	22 × 35	0.15	1.67	EKMM161VSN561MP35S		180	22 × 20	0.15	0.80	EKMM201VSN181MP20S
	560	25.4 × 30	0.15	1.67	EKMM161VSN561MQ30S		220	25.4 × 20	0.15	0.85	EKMM201VSN221MQ20S
	560	30 × 25	0.15	1.67	EKMM161VSN561MR25S		270	22 × 25	0.15	1.10	EKMM201VSN271MP25S
	560	35 × 20	0.15	1.46	EKMM161VSN561MA20S		270	30 × 20	0.15	1.05	EKMM201VSN271MR20S
	680	22 × 40	0.15	1.82	EKMM161VSN681MP40S		330	22 × 30	0.15	1.25	EKMM201VSN331MP30S
	680	25.4 × 30	0.15	1.82	EKMM161VSN681MQ30S		330	25.4 × 25	0.15	1.25	EKMM201VSN331MQ25S
	680	30 × 25	0.15	1.82	EKMM161VSN681MR25S		330	30 × 20	0.15	1.10	EKMM201VSN331MR20S
	680	35 × 20	0.15	1.51	EKMM161VSN681MA20S		390	22 × 30	0.15	1.35	EKMM201VSN391MP30S
	820	22 × 45	0.15	2.04	EKMM161VSN821MP45S		390	25.4 × 25	0.15	1.35	EKMM201VSN391MQ25S
	820	25.4 × 35	0.15	2.04	EKMM161VSN821MQ35S		390	35 × 20	0.15	1.30	EKMM201VSN391MA20S
	820	30 × 30	0.15	2.04	EKMM161VSN821MR30S		470	22 × 35	0.15	1.50	EKMM201VSN471MP35S
	820	35 × 25	0.15	2.04	EKMM161VSN821MA25S		470	25.4 × 30	0.15	1.50	EKMM201VSN471MQ30S
	1,000	22 × 50	0.15	2.25	EKMM161VSN102MP50S		470	30 × 25	0.15	1.50	EKMM201VSN471MR25S
	1,000	25.4 × 40	0.15	2.25	EKMM161VSN102MQ40S		470	35 × 20	0.15	1.41	EKMM201VSN471MA20S
	1,000	30 × 30	0.15	2.25	EKMM161VSN102MR30S		560	22 × 40	0.15	1.67	EKMM201VSN561MP40S
	1,000	35 × 25	0.15	2.25	EKMM161VSN102MA25S		560	25.4 × 30	0.15	1.67	EKMM201VSN561MQ30S
	1,200	25.4 × 45	0.15	2.49	EKMM161VSN122MQ45S		560	30 × 25	0.15	1.67	EKMM201VSN561MR25S
	1,200	30 × 35	0.15	2.49	EKMM161VSN122MR35S		680	22 × 45	0.15	1.78	EKMM201VSN681MP45S
	1,200	35 × 30	0.15	2.49	EKMM161VSN122MA30S		680	25.4 × 35	0.15	1.78	EKMM201VSN681MQ35S
	1,500	25.4 × 60	0.15	2.97	EKMM161VSN152MQ60S		680	30 × 30	0.15	1.78	EKMM201VSN681MR30S
	1,500	30 × 40	0.15	2.84	EKMM161VSN152MR40S		680	35 × 25	0.15	1.78	EKMM201VSN681MA25S
	1,500	35 × 30	0.15	2.84	EKMM161VSN152MA30S		820	25.4 × 45	0.15	2.04	EKMM201VSN821MQ45S
	1,800	30 × 45	0.15	3.32	EKMM161VSN182MR45S		820	30 × 30	0.15	2.04	EKMM201VSN821MR30S
	1,800	35 × 35	0.15	3.00	EKMM161VSN182MA35S		820	35 × 25	0.15	2.04	EKMM201VSN821MA25S
	2,200	30 × 60	0.15	3.86	EKMM161VSN222MR60S		1,000	25.4 × 50	0.15	2.30	EKMM201VSN102MQ50S
	2,200	35 × 45	0.15	3.50	EKMM161VSN222MA45S		1,000	30 × 35	0.15	2.30	EKMM201VSN102MR35S
	2,700	35 × 50	0.15	4.00	EKMM161VSN272MA50S		1,000	35 × 30	0.15	2.30	EKMM201VSN102MA30S
	3,300	35 × 60	0.15	4.63	EKMM161VSN332MA60S		1,200	25.4 × 60	0.15	2.66	EKMM201VSN122MQ60S
180	180	22 × 20	0.15	0.80	EKMM181VSN181MP20S		1,200	30 × 40	0.15	2.65	EKMM201VSN122MR40S
	220	25.4 × 20	0.15	0.90	EKMM181VSN221MQ20S		1,200	35 × 35	0.15	2.65	EKMM201VSN122MA35S
	270	22 × 25	0.15	1.00	EKMM181VSN271MP25S		1,500	30 × 50	0.15	3.08	EKMM201VSN152MR50S
	270	25.4 × 20	0.15	0.95	EKMM181VSN271MQ20S		1,500	35 × 40	0.15	3.08	EKMM201VSN152MA40S
	330	22 × 25	0.15	1.20	EKMM181VSN331MP25S		1,800	30 × 60	0.15	3.49	EKMM201VSN182MR60S
	330	25.4 × 25	0.15	1.16	EKMM181VSN331MQ25S		1,800	35 × 45	0.15	3.48	EKMM201VSN182MA45S
	330	30 × 20	0.15	1.15	EKMM181VSN331MR20S		2,200	35 × 50	0.15	3.78	EKMM201VSN222MA50S
	390	22 × 30	0.15	1.35	EKMM181VSN391MP30S	220	150	22 × 20	0.15	0.67	EKMM221VSN151MP20S
	390	25.4 × 25	0.15	1.35	EKMM181VSN391MQ25S		180	25.4 × 20	0.15	0.76	EKMM221VSN181MQ20S
	390	30 × 20	0.15	1.20	EKMM181VSN391MR20S		220	22 × 25	0.15	1.00	EKMM221VSN221MP25S
	470	22 × 35	0.15	1.50	EKMM181VSN471MP35S		220	25.4 × 20	0.15	0.84	EKMM221VSN221MQ20S
	470	25.4 × 30	0.15	1.50	EKMM181VSN471MQ30S		270	22 × 30	0.15	1.15	EKMM221VSN271MP30S
	470	30 × 25	0.15	1.50	EKMM181VSN471MR25S		270	25.4 × 25	0.15	1.08	EKMM221VSN271MQ25S
	470	35 × 20	0.15	1.36	EKMM181VSN471MA20S		270	30 × 20	0.15	0.98	EKMM221VSN271MR20S
	560	22 × 40	0.15	1.67	EKMM181VSN561MP40S		330	22 × 35	0.15	1.25	EKMM221VSN331MP35S
	560	25.4 × 30	0.15	1.67	EKMM181VSN561MQ30S		330	25.4 × 25	0.15	1.25	EKMM221VSN331MQ25S
	560	30 × 25	0.15	1.67	EKMM181VSN561MR25S		330	35 × 20	0.15	1.13	EKMM221VSN331MA20S
	560	35 × 20	0.15	1.43	EKMM181VSN561MA20S		390	22 × 35	0.15	1.40	EKMM221VSN391MP35S
	680	22 × 45	0.15	1.78	EKMM181VSN681MP45S		390	25.4 × 30	0.15	1.40	EKMM221VSN391MQ30S
	680	25.4 × 35	0.15	1.78	EKMM181VSN681MQ35S		390	30 × 25	0.15	1.36	EKMM221VSN391MR25S
	680	30 × 30	0.15	1.78	EKMM181VSN681MR30S		390	35 × 20	0.15	1.23	EKMM221VSN391MA20S
	680	35 × 25	0.15	1.83	EKMM181VSN681MA25S		470	22 × 40	0.15	1.51	EKMM221VSN471MP40S
	820	22 × 50	0.15	2.04	EKMM181VSN821MP50S		470	25.4 × 35	0.15	1.54	EKMM221VSN471MQ35S
	820	25.4 × 40	0.15	2.04	EKMM181VSN821MQ40S		470	30 × 25	0.15	1.50	EKMM221VSN471MR25S
	820	30 × 30	0.15	2.04	EKMM181VSN821MR30S		560	22 × 45	0.15	1.70	EKMM221VSN561MP45S
	820	35 × 25	0.15	2.04	EKMM181VSN821MA25S		560	25.4 × 40	0.15	1.72	EKMM221VSN561MQ40S
	1,000	25.4 × 45	0.15	2.30	EKMM181VSN102MQ45S		560	30 × 30	0.15	1.70	EKMM221VSN561MR30S
	1,000	30 × 35	0.15	2.30	EKMM181VSN102MR35S		560	35 × 25	0.15	1.71	EKMM221VSN561MA25S
	1,000	35 × 30	0.15	2.30	EKMM181VSN102MA30S		680	25.4 × 45	0.15	1.94	EKMM221VSN681MQ45S

◆STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.	WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.
220	680	30 × 35	0.15	1.93	EKMM221VSN681MR35S	315	220	25.4 × 30	0.15	1.04	EKMM3B1VSN221MQ30S
	680	35 × 25	0.15	1.89	EKMM221VSN681MA25S		220	30 × 25	0.15	1.04	EKMM3B1VSN221MR25S
	820	25.4 × 50	0.15	2.18	EKMM221VSN821MQ50S		220	35 × 20	0.15	0.90	EKMM3B1VSN221MA20S
	820	30 × 40	0.15	2.19	EKMM221VSN821MR40S		270	22 × 45	0.15	1.16	EKMM3B1VSN271MP45S
	820	35 × 30	0.15	2.16	EKMM221VSN821MA30S		270	25.4 × 35	0.15	1.16	EKMM3B1VSN271MQ35S
	1,000	25.4 × 60	0.15	2.54	EKMM221VSN102MQ60S		270	30 × 25	0.15	1.16	EKMM3B1VSN271MR25S
	1,000	30 × 45	0.15	2.50	EKMM221VSN102MR45S		270	35 × 25	0.15	1.15	EKMM3B1VSN271MA25S
	1,000	35 × 35	0.15	2.44	EKMM221VSN102MA35S		330	22 × 50	0.15	1.33	EKMM3B1VSN331MP50S
	1,200	30 × 50	0.15	2.81	EKMM221VSN122MR50S		330	25.4 × 40	0.15	1.33	EKMM3B1VSN331MQ40S
	1,200	35 × 40	0.15	2.79	EKMM221VSN122MA40S		330	30 × 30	0.15	1.33	EKMM3B1VSN331MR30S
	1,500	30 × 60	0.15	3.30	EKMM221VSN152MR60S		330	35 × 25	0.15	1.33	EKMM3B1VSN331MA25S
	1,500	35 × 45	0.15	3.22	EKMM221VSN152MA45S		390	25.4 × 45	0.15	1.47	EKMM3B1VSN391MQ45S
	1,800	35 × 50	0.15	3.63	EKMM221VSN182MA50S		390	30 × 35	0.15	1.47	EKMM3B1VSN391MR35S
	2,200	35 × 60	0.15	4.23	EKMM221VSN222MA60S		390	35 × 30	0.15	1.47	EKMM3B1VSN391MA30S
250	120	22 × 20	0.15	0.60	EKMM251VSN121MP20S	350	470	25.4 × 50	0.15	1.70	EKMM3B1VSN471MQ50S
	150	25.4 × 20	0.15	0.74	EKMM251VSN151MQ20S		470	30 × 40	0.15	1.70	EKMM3B1VSN471MR40S
	180	22 × 25	0.15	0.78	EKMM251VSN181MP25S		470	35 × 30	0.15	1.70	EKMM3B1VSN471MA30S
	180	25.4 × 20	0.15	0.75	EKMM251VSN181MQ20S		560	30 × 45	0.15	2.05	EKMM3B1VSN561MR45S
	220	22 × 25	0.15	1.00	EKMM251VSN221MP25S		560	35 × 35	0.15	2.05	EKMM3B1VSN561MA35S
	220	25.4 × 25	0.15	0.95	EKMM251VSN221MQ25S		680	30 × 50	0.15	2.17	EKMM3B1VSN681MR50S
	220	30 × 20	0.15	0.95	EKMM251VSN221MR20S		680	35 × 40	0.15	2.17	EKMM3B1VSN681MA40S
	270	22 × 30	0.15	1.18	EKMM251VSN271MP30S		820	35 × 45	0.15	2.20	EKMM3B1VSN821MA45S
	270	25.4 × 25	0.15	1.18	EKMM251VSN271MQ25S		1,000	35 × 60	0.15	2.55	EKMM3B1VSN102MA60S
	270	30 × 20	0.15	1.00	EKMM251VSN271MR20S		56	22 × 20	0.15	0.41	EKMM351VSN560MP20S
	330	22 × 35	0.15	1.30	EKMM251VSN331MP35S		68	25.4 × 20	0.15	0.46	EKMM351VSN680MQ20S
	330	25.4 × 30	0.15	1.30	EKMM251VSN331MQ30S		82	22 × 25	0.15	0.55	EKMM351VSN820MP25S
	330	30 × 25	0.15	1.30	EKMM251VSN331MR25S		82	25.4 × 20	0.15	0.51	EKMM351VSN820MQ20S
	330	35 × 20	0.15	1.16	EKMM251VSN331MA20S		100	22 × 25	0.15	0.69	EKMM351VSN101MP25S
	390	22 × 40	0.15	1.49	EKMM251VSN391MP40S		100	30 × 20	0.15	0.60	EKMM351VSN101MR20S
	390	25.4 × 35	0.15	1.49	EKMM251VSN391MQ35S	400	120	22 × 30	0.15	0.75	EKMM351VSN121MP30S
	390	30 × 25	0.15	1.49	EKMM251VSN391MR25S		120	25.4 × 25	0.15	0.75	EKMM351VSN121MQ25S
	470	22 × 45	0.15	1.65	EKMM251VSN471MP45S		120	30 × 20	0.15	0.65	EKMM351VSN121MR20S
	470	25.4 × 35	0.15	1.65	EKMM251VSN471MQ35S		150	22 × 35	0.15	0.82	EKMM351VSN151MP35S
	470	30 × 30	0.15	1.65	EKMM251VSN471MR30S		150	25.4 × 30	0.15	0.83	EKMM351VSN151MQ30S
	470	35 × 25	0.15	1.65	EKMM251VSN471MA25S		150	30 × 25	0.15	0.82	EKMM351VSN151MR25S
	560	22 × 50	0.15	1.67	EKMM251VSN561MP50S		150	35 × 20	0.15	0.76	EKMM351VSN151MA20S
	560	25.4 × 40	0.15	1.80	EKMM251VSN561MQ40S		180	22 × 40	0.15	0.92	EKMM351VSN181MP40S
	560	30 × 30	0.15	1.80	EKMM251VSN561MR30S		180	25.4 × 30	0.15	0.92	EKMM351VSN181MQ30S
	560	35 × 25	0.15	1.80	EKMM251VSN561MA25S		180	30 × 25	0.15	0.90	EKMM351VSN181MR25S
	680	25.4 × 50	0.15	2.00	EKMM251VSN681MQ50S		220	22 × 45	0.15	1.05	EKMM351VSN221MP45S
	680	30 × 35	0.15	2.00	EKMM251VSN681MR35S		220	25.4 × 35	0.15	1.04	EKMM351VSN221MQ35S
	680	35 × 30	0.15	2.00	EKMM251VSN681MA30S		220	30 × 30	0.15	1.02	EKMM351VSN221MR30S
	820	25.4 × 60	0.15	2.20	EKMM251VSN821MQ60S		220	35 × 25	0.15	1.04	EKMM351VSN221MA25S
	820	30 × 40	0.15	2.30	EKMM251VSN821MR40S		270	22 × 50	0.15	1.16	EKMM351VSN271MP50S
	820	35 × 35	0.15	2.30	EKMM251VSN821MA35S		270	25.4 × 40	0.15	1.18	EKMM351VSN271MQ40S
	1,000	30 × 50	0.15	2.47	EKMM251VSN102MR50S		270	30 × 30	0.15	1.17	EKMM351VSN271MR30S
	1,000	35 × 40	0.15	2.47	EKMM251VSN102MA40S		270	35 × 25	0.15	1.20	EKMM351VSN271MA25S
	1,200	30 × 60	0.15	2.85	EKMM251VSN122MR60S		330	25.4 × 45	0.15	1.29	EKMM351VSN331MQ45S
	1,200	35 × 45	0.15	2.60	EKMM251VSN122MA45S		330	30 × 35	0.15	1.34	EKMM351VSN331MR35S
	1,500	35 × 50	0.15	3.00	EKMM251VSN152MA50S		330	35 × 30	0.15	1.22	EKMM351VSN331MA30S
	1,800	35 × 60	0.15	3.42	EKMM251VSN182MA60S		390	25.4 × 50	0.15	1.51	EKMM351VSN391MQ50S
315	68	22 × 20	0.15	0.45	EKMM3B1VSN680MP20S		390	30 × 40	0.15	1.51	EKMM351VSN391MR40S
	82	22 × 20	0.15	0.47	EKMM3B1VSN820MP20S		390	35 × 35	0.15	1.47	EKMM351VSN391MA35S
	100	22 × 25	0.15	0.61	EKMM3B1VSN101MP25S		470	25.4 × 60	0.15	1.66	EKMM351VSN471MQ60S
	100	25.4 × 20	0.15	0.56	EKMM3B1VSN101MQ20S		470	30 × 45	0.15	1.65	EKMM351VSN471MR45S
	120	22 × 25	0.15	0.75	EKMM3B1VSN121MP25S		470	35 × 35	0.15	1.69	EKMM351VSN471MA35S
	120	25.4 × 20	0.15	0.62	EKMM3B1VSN121MQ20S		560	30 × 50	0.15	1.85	EKMM351VSN561MR50S
	120	30 × 20	0.15	0.65	EKMM3B1VSN121MR20S		560	35 × 40	0.15	1.90	EKMM351VSN561MA40S
	150	22 × 30	0.15	0.82	EKMM3B1VSN151MP30S		680	30 × 60	0.15	2.15	EKMM351VSN681MR60S
	150	25.4 × 25	0.15	0.82	EKMM3B1VSN151MQ25S		680	35 × 50	0.15	1.99	EKMM351VSN681MA50S
	150	30 × 20	0.15	0.70	EKMM3B1VSN151MR20S		820	35 × 60	0.15	2.31	EKMM351VSN821MA60S
	150	35 × 20	0.15	0.76	EKMM3B1VSN151MA20S		47	22 × 20	0.15	0.37	EKMM401VSN470MP20S
	180	22 × 35	0.15	0.92	EKMM3B1VSN181MP35S		56	25.4 × 20	0.15	0.42	EKMM401VSN560MQ20S
	180	25.4 × 25	0.15	0.92	EKMM3B1VSN181MQ25S		68	22 × 25	0.15	0.50	EKMM401VSN680MP25S
	180	30 × 25	0.15	0.90	EKMM3B1VSN181MR25S		68	25.4 × 20	0.15	0.46	EKMM401VSN680MQ20S
	180	35 × 20	0.15	0.85	EKMM3B1VSN181MA20S		82	22 × 25	0.15	0.64	EKMM401VSN820MP25S
	220	22 × 40	0.15	1.04	EKMM3B1VSN221MP40S		82	30 × 20	0.15	0.55	EKMM401VSN820MR20S

KMM Series

◆STANDARD RATINGS

WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.	WV (V _{dc})	Cap (μF)	Case size φD×L(mm)	tan δ	Rated ripple current (Arms/ 105°C, 120Hz)	Part No.
400	100	22 × 30	0.15	0.70	EKMM401VSN101MP30S	420	180	25.4 × 35	0.20	0.95	EKMM421VSN181MQ35S
	100	25.4 × 25	0.15	0.70	EKMM401VSN101MQ25S		180	30 × 30	0.20	0.95	EKMM421VSN181MR30S
	100	30 × 20	0.15	0.60	EKMM401VSN101MR20S		180	35 × 25	0.20	0.94	EKMM421VSN181MA25S
	120	22 × 35	0.15	0.75	EKMM401VSN121MP35S		220	22 × 50	0.20	1.10	EKMM421VSN221MP50S
	120	25.4 × 25	0.15	0.75	EKMM401VSN121MQ25S		220	25.4 × 45	0.20	1.10	EKMM421VSN221MQ45S
	120	30 × 25	0.15	0.73	EKMM401VSN121MR25S		220	30 × 35	0.20	1.10	EKMM421VSN221MR35S
	120	35 × 20	0.15	0.75	EKMM401VSN121MA20S		220	35 × 25	0.20	1.10	EKMM421VSN221MA25S
	150	22 × 40	0.15	0.88	EKMM401VSN151MP40S		270	25.4 × 50	0.20	1.22	EKMM421VSN271MQ50S
	150	25.4 × 30	0.15	0.88	EKMM401VSN151MQ30S		270	30 × 40	0.20	1.22	EKMM421VSN271MR40S
	150	30 × 25	0.15	0.88	EKMM401VSN151MR25S		270	35 × 30	0.20	1.22	EKMM421VSN271MA30S
	150	35 × 20	0.15	0.80	EKMM401VSN151MA20S		330	25.4 × 60	0.20	1.41	EKMM421VSN331MQ60S
	180	22 × 45	0.15	0.98	EKMM401VSN181MP45S		330	30 × 45	0.20	1.45	EKMM421VSN331MR45S
	180	25.4 × 35	0.15	0.98	EKMM401VSN181MQ35S		330	35 × 35	0.20	1.45	EKMM421VSN331MA35S
	180	30 × 30	0.15	0.98	EKMM401VSN181MR30S		390	30 × 50	0.20	1.55	EKMM421VSN391MR50S
	180	35 × 25	0.15	0.98	EKMM401VSN181MA25S		390	35 × 40	0.20	1.55	EKMM421VSN391MA40S
	220	22 × 50	0.15	1.10	EKMM401VSN221MP50S		470	30 × 60	0.20	1.79	EKMM421VSN471MR60S
	220	25.4 × 40	0.15	1.10	EKMM401VSN221MQ40S		470	35 × 45	0.20	1.90	EKMM421VSN471MA45S
	220	30 × 30	0.15	1.10	EKMM401VSN221MR30S		560	35 × 50	0.20	2.15	EKMM421VSN561MA50S
	220	35 × 25	0.15	1.10	EKMM401VSN221MA25S		680	35 × 60	0.20	2.27	EKMM421VSN681MA60S
	270	25.4 × 45	0.15	1.22	EKMM401VSN271MQ45S	450	56	22 × 25	0.20	0.40	EKMM451VSN560MP25S
	270	30 × 35	0.15	1.22	EKMM401VSN271MR35S		68	22 × 30	0.20	0.53	EKMM451VSN680MP30S
	270	35 × 30	0.15	1.22	EKMM401VSN271MA30S		68	25.4 × 25	0.20	0.50	EKMM451VSN680MQ25S
	330	25.4 × 50	0.15	1.44	EKMM401VSN331MQ50S		82	22 × 30	0.20	0.64	EKMM451VSN820MP30S
	330	30 × 40	0.15	1.44	EKMM401VSN331MR40S		82	25.4 × 25	0.20	0.64	EKMM451VSN820MQ25S
	330	35 × 30	0.15	1.44	EKMM401VSN331MA30S		100	22 × 35	0.20	0.69	EKMM451VSN101MP35S
	390	25.4 × 60	0.15	1.51	EKMM401VSN391MQ60S		100	25.4 × 30	0.20	0.69	EKMM451VSN101MQ30S
	390	30 × 45	0.15	1.60	EKMM401VSN391MR45S		100	30 × 25	0.20	0.64	EKMM451VSN101MR25S
	390	35 × 35	0.15	1.60	EKMM401VSN391MA35S		120	22 × 40	0.20	0.80	EKMM451VSN121MP40S
	470	30 × 50	0.15	1.90	EKMM401VSN471MR50S		120	25.4 × 30	0.20	0.80	EKMM451VSN121MQ30S
	470	35 × 40	0.15	1.90	EKMM401VSN471MA40S		120	30 × 25	0.20	0.80	EKMM451VSN121MR25S
	560	30 × 60	0.15	2.10	EKMM401VSN561MR60S		120	35 × 25	0.20	0.73	EKMM451VSN121MA25S
	560	35 × 45	0.15	2.12	EKMM401VSN561MA45S		150	22 × 45	0.20	0.88	EKMM451VSN151MP45S
	680	35 × 60	0.15	2.27	EKMM401VSN681MA60S		150	25.4 × 35	0.20	0.88	EKMM451VSN151MQ35S
420	47	22 × 20	0.20	0.37	EKMM421VSN470MP20S		150	30 × 30	0.20	0.88	EKMM451VSN151MR30S
	56	25.4 × 20	0.20	0.42	EKMM421VSN560MQ20S		150	35 × 25	0.20	0.75	EKMM451VSN151MA25S
	68	22 × 25	0.20	0.50	EKMM421VSN680MP25S		180	22 × 50	0.20	1.00	EKMM451VSN181MP50S
	68	25.4 × 20	0.20	0.46	EKMM421VSN680MQ20S		180	25.4 × 40	0.20	1.00	EKMM451VSN181MQ40S
	82	22 × 25	0.20	0.64	EKMM421VSN820MP25S		180	30 × 30	0.20	1.00	EKMM451VSN181MR30S
	82	25.4 × 25	0.20	0.58	EKMM421VSN820MQ25S		220	25.4 × 45	0.20	1.12	EKMM451VSN221MQ45S
	82	30 × 20	0.20	0.53	EKMM421VSN820MR20S		220	30 × 35	0.20	1.12	EKMM451VSN221MR35S
	100	22 × 30	0.20	0.70	EKMM421VSN101MP30S		220	35 × 30	0.20	1.12	EKMM451VSN221MA30S
	100	25.4 × 25	0.20	0.70	EKMM421VSN101MQ25S		270	25.4 × 60	0.20	1.18	EKMM451VSN271MQ60S
	100	30 × 20	0.20	0.59	EKMM421VSN101MR20S		270	30 × 40	0.20	1.28	EKMM451VSN271MR40S
	120	22 × 35	0.20	0.75	EKMM421VSN121MP35S		270	35 × 35	0.20	1.28	EKMM451VSN271MA35S
	120	25.4 × 30	0.20	0.75	EKMM421VSN121MQ30S		330	30 × 50	0.20	1.45	EKMM451VSN331MR50S
	120	30 × 25	0.20	0.73	EKMM421VSN121MR25S		330	35 × 40	0.20	1.45	EKMM451VSN331MA40S
	120	35 × 20	0.20	0.67	EKMM421VSN121MA20S		390	30 × 60	0.20	1.51	EKMM451VSN391MR60S
	150	22 × 40	0.20	0.88	EKMM421VSN151MP40S		390	35 × 40	0.20	1.55	EKMM451VSN391MA40S
	150	25.4 × 35	0.20	0.88	EKMM421VSN151MQ35S		470	35 × 50	0.20	1.85	EKMM451VSN471MA50S
	150	30 × 25	0.20	0.88	EKMM421VSN151MR25S		560	35 × 60	0.20	1.91	EKMM451VSN561MA60S
	180	22 × 45	0.20	0.95	EKMM421VSN181MP45S						

◆RATED RIPPLE CURRENT MULTIPLIERS

●Frequency Multipliers

Frequency(Hz)	50	120	300	1k	10k	50k
160 to 250V _{dc}	0.81	1.00	1.17	1.32	1.45	1.50
315 to 450V _{dc}	0.77	1.00	1.16	1.30	1.41	1.43

The endurance of capacitors is reduced with internal heating produced by ripple current at the rate of halving the lifetime with every 5°C rise. When long life performance is required in actual use, the rms ripple current has to be reduced.