

Specification Sheet

Part Number: T120R5H4



Heavy Duty Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66, Green, 500/pkg

Article Number	111-12052
Type	T120R
Color	Green (GN)
Features & Benefits	•Engineered and manufactured for maximum performance and quality. •Made from 100% high-quality plastic to ensure efficient recycling. •Inside serration for a strong grip onto bundles. •Easy application either manually or with a tensioning tool. •Bent tail allows for simpler insertion.
Quantity Per	bag

Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
---------------------	---

Short Description	Heavy Duty Cable Tie, 15.2" Long, UL Rated, 120lb Tensile Strength, PA66, Green, 500/pkg
Global Part Name	T120R-PA66-GN
Minimum Tensile Strength (Imperial)	120.0
Minimum Tensile Strength (Metric)	535.0
Length L (Imperial)	15.2
Length L (Metric)	387.0
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.30
Width W (Metric)	7.6
Bundle Diameter Min (Imperial)	0.20
Bundle Diameter Min (Metric)	5.0
Bundle Diameter Max (Imperial)	4.1
Bundle Diameter Max (Metric)	104.1

Material	Polyamide 6.6 (PA66)	
Material Shortcut	PA66	
US MIL SPEC	MS3367-3-5	
SAE-AS33671	Flammability	
UL 94 V2	Halogen free	
Yes	Operating Temperature (Metric)	
-40°F to +185°F (-40°C to +85°C)	ROHS Complaint	
Yes	Certification/Specification WEB	
CAGE Code 53421 UL-ZODZ.E64139	UL Recognized (US)	
Yes	UL Listed (US and Canada)	
Yes	UL Recognized (US and Canada)	
Yes	UL Listed (US	
Yes		
Package Quantity(Imperial)	500	
Package Quantity (Metric)	500	

Customs Number

3926909988