

Part Number: 1727040182

Product Description: FCT Metal Backshell for D-Sub Connector, Shell Size 1, Straight Cable Outlet, with Rubber Bushing and #4-40

Knurled Thumb Screws

Series Number: 172704

Status: Active

Product Category: D-Sub Backshells

Engineering Number: FMH1R



Documents & Resources

Drawings

Drawing 1727040182_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | Not Relevant |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Relevant |
| REACH SVHC | Contains Lead per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| Status | Active |
|----------------|---|
| Category | D-Sub Backshells |
| Series | 172704 |
| Description | FCT Metal Backshell for D-Sub Connector, Shell Size 1, Straight Cable Outlet, with Rubber Bushing and #4-40 Knurled Thumb Screws |
| Magnetic | Yes |
| Product Family | FCT D-Sub Connectors |
| Product Name | FCT Products |
| Туре | Rugged Metal |
| UPC | 889056062589 |

Electrical

| Shield Type | Solid Metal |
|-------------|-------------|
| Shielded | Yes |

Physical

| Cable Diameter | 5.00-8.00mm |
|-------------------------------|--------------------------|
| Material - Backshell | Zinc Die-cast |
| Material - Bushing | TPE |
| Material - Screw | Brass |
| Mounting Style | Knurled Thumb Screw Lock |
| Net Weight | 45.400/g |
| Orientation | Straight |
| Packaging Type | Carton |
| Plating - Backshell | Nickel |
| Temperature Range - Operating | -35° to +100°C |
| Thread Size | 4-40 UNC |
| Thread Type | Standard |
| Tightening Test Torque | 40 Ncm |

| Waterproof / Dustproof | No |
|------------------------|----|
|------------------------|----|

Use with Part(s)

| Description | Part Number |
|-------------|-------------------|
| Use With | FCT D-Sub, Size 1 |

This document was generated on Sep 19, 2024