



Switches > Battery Disconnect Switches > Battery Disconnect, 200A, 1 Pole



Operating Voltage: 32 VDC

Switch Main Contact Current Rating: 250 A

Number of Poles: 1

Termination Thread Size: M8

Number of Auxiliary Contacts: 0

[All Battery Disconnect, 200A, 1 Pole \(30\)](#)

Features

Product Type Features

Sealed Device	Yes
---------------	-----

Configuration Features

Number of Poles	1
Number of Auxiliary Contacts	0
Switch Keying Option	Not Removable

Electrical Characteristics

Operating Voltage	32 VDC
Switch Main Contact Current Rating	250 A

Body Features

Operating Handle Color	Black
------------------------	-------

Mechanical Attachment

Termination Thread Size	M8
Switch Mounting Option	Round Flange
Operating Handle Type	Double Wing

Dimensions

--	--



Centerline Between Flange Screw Holes	38 mm[1.5 in]
Screw Hole Diameter	7 mm[.276 in]

Usage Conditions

Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]
-----------------------------	---------------------------

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) SVHC > Threshold: Pb (2% in Component part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # K1130516
Battery Disconnect 35-221-100-R



TE Part # K1146614
Battery Disconnect 35-210-100-R-900

Also in the Series | KISSLING Series 35



Battery Disconnect Switches(164)



Rotary Switches(6)


Customers Also Bought




TE Part #160138
PIDG RING TONGUE



TE Part #170341-3
FF 250 TAB 14-12AWG TPBR
WITHOUT LATCH



TE Part #170258-2
FF 250 REC 14-12AWG TPBR
REREELING



TE Part #180321-000
2022E0421-9X



TE Part #T4113001041-000
M12,MALE,RA,A CODE,4P,PG7,GOLD



TE Part #M902-2194
BKSHL, 9SZ, CBL SZ .570-.710, HD10



TE Part #DTP04-2P-E003
REC, 2P, GRY, N, CAP



TE Part #K1131877
Battery Disconnect 35-210-141-R



TE Part #656077-000
CWT-3803



Documents

Product Drawings

Battery Disconnecter 35-210-041-S

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35-210-041-S_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35-210-041-S_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35-210-041-S_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

KISSLING SINGLE POLE BI-STABLE RELAYS Series 30 / 300A

English

KISSLING BATTERY DISCONNECTOR Series 35 / 200A

English