TE Internal #: 1-1337504-0

TE Internal Description: BNC BHSkt + Tag 750hm Silver Pltd

View on TE.com >



#### Connectors > RF Connectors > Coax Connectors



RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [ .572 in ]

Impedance:  $75 \Omega$ 

RF Connector Coupling Mechanism: Bayonet

## **Features**

# **Product Type Features**

RF Interface	BNC
RF Connector Style	Jack
Connector System	Cable-to-Panel
Sealable	No

## **Configuration Features**

Number of Positions	1
Number of Coaxial Contacts	1

#### **Electrical Characteristics**

Impedance	75 Ω	

### **Body Features**

Cable Connector Orientation	Straight
Body Material	Brass
Body Plating Material	Silver

#### **Contact Features**

RF Connector Center Contact Plating Material	Silver
RF Connector Center Contact Material	Brass

#### **Termination Features**

Termination Method to Wire & Cable	Solder Terminal	
------------------------------------	-----------------	--

#### Mechanical Attachment



Panel Mount Feature Type	Hex Nut
Panel Attachment Style	Front Mount
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Panel Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Dimensions	
Panel Thickness (Recommended)	1.5 – 2.9 mm[.059 – .114 in]
RF Connector Mated Outer Diameter (Approximate)	14.53 mm[.572 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	2 GHz
Packaging Features	
Packaging Quantity	50
Packaging Method	Box
Other	
Lockwasher Material	Brass
Grade	Professional
Dielectric Material	PTFE

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUN 2016 (169) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.



#### Solder Process Capability

Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Customers Also Bought





















#### **Documents**

#### **CAD Files**

Customer View Model ENG\_CVM\_CVM\_1-1337504-0\_C.2d\_dxf.zip

English



3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1337504-0\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1337504-0\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.