

DEHR32E331KA2B

“ # ” indicates a package specification code.


Available

Flow OK

Complies with RoHS

< List of part numbers with package codes >
DEHR32E331KA2B

Shape



Lead Code	Coating Extension e	ø d	Style
A2, A3, A4	Up to the end of crimp	0.6±0.05	Fig. 1
C3	3.0 max.	0.6±0.05	Fig. 2



L size or outer diameter D (mm)	6.0 mm max.
Lead spacing F	5 ±1.0mm
Product thickness T	4.0mm max.
Lead diameter d	0.6 ±0.05mm
Paint dripping e	Up to the end of crimp

Specifications

Capacitance	330pF ±10%
Rated voltage	250Vdc
Temperature characteristics (complied standard)	R(JIS)
Capacitance change rate (1)	±15%(-25 to 85℃)
Capacitance change rate (2)	+15/-30%(85 to 125℃)
Temperature range of temperature characteristics	-25 to 125℃
Operating temperature range	-25 to 125℃

References

Packaging	Specifications	Minimum quantity
	Packing in bulk	500

⚠ Attention

- 1.This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it ’ s specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2.This datasheet has only typical specifications because there is no space for detailed specifications.
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.