





RoHS



适用线路板 (PCB LAYOUT)

Model No.	Pin	A	B	C	D
WAFER-XH2.54-2PZZ-W	2	2.50	7.50		6.20
WAFER-XH2.54-3PZZ-W	3	5.00	10.00	3.00	8.70
WAFER-XH2.54-4PZZ-W	4	7.50	12.50	5.50	11.20
WAFER-XH2.54-5PZZ-W	5	10.00	15.00	8.00	13.70
WAFER-XH2.54-6PZZ-W	6	12.50	17.50	10.50	16.20
WAFER-XH2.54-7PZZ-W	7	15.00	20.00	13.00	18.70
WAFER-XH2.54-8PZZ-W	8	17.50	22.50	15.50	21.20
WAFER-XH2.54-9PZZ-W	9	20.00	25.00	18.00	23.70
WAFER-XH2.54-10PZZ-W	10	22.50	27.50	20.50	26.20
WAFER-XH2.54-11PZZ-W	11	25.00	30.00	23.00	28.70
WAFER-XH2.54-12PZZ-W	12	27.50	32.50	25.50	31.20
WAFER-XH2.54-13PZZ-W	13	30.00	35.00	28.00	33.70
WAFER-XH2.54-14PZZ-W	14	32.50	37.50	30.50	36.20
WAFER-XH2.54-15PZZ-W	15	35.00	40.00	33.00	38.70
WAFER-XH2.54-16PZZ-W	16	37.50	42.50	35.50	41.20
WAFER-XH2.54-17PZZ-W	17	40.00	45.00	38.00	43.70
WAFER-XH2.54-18PZZ-W	18	42.50	47.50	40.50	46.20
WAFER-XH2.54-19PZZ-W	19	45.00	50.00	43.00	48.70
WAFER-XH2.54-20PZZ-W	20	47.50	52.50	45.50	51.20

Specifications/技术规格:

- 1.Poles/线数: 2~20P
- 2.Wire range/适用线规: AGW 28#~22#
- 3.Applicable PC board thickness/适用PC板厚度: 1.6mm
- 4.Current rating/额定电流: 3.0A
- 5.Voltage rating/额定电压: 250V DC/AC
- 6.Insulation Resistance/绝缘电阻: 1000MΩ Min
- 7.Dielectric Withstanding/ 耐电压: 1000V AC/minute
- 8.Contact Resistance/ 接触电阻: 30mΩ Max
- 9.Operating Temperature/ 工作温度: -25℃ to +85℃

⑧	Terminal			Brass	Plating Sn
⑨	Housing		1	PA66	White
NO.	Name	Number	Qty	Materil	Remarks
ZHONGDI® Zhongdi Electronic Technology Co., Ltd					
众迪					
design		date		name	WAFER CONNECTOR
Review		date			
Approved		date		model	WAFER-XH2.54-□□PZZ-W
number:					
1:1	unit	mm	gape number	A4	