



HEAT SHRINK TUBING



✓ Active

TE CONNECTIVITY (TE)
TAT-125-3/8-0-1.5IN
[Raychem](#) | [TAT-125](#)

TAT-125-3/8-0-1.5IN
TE Internal Number: 145128-000
Alias ID: 9-1199143-3

[EU RoHS Compliant](#)
[EU ELV Compliant](#)

Wall Type Dual
Resistant To Cut-Through, Flexing, Fluids, Mechanical Damage
Product Source US
Packaging Method Piece
Shrink Ratio 2:1

DOCUMENTATION

Catalog Pages/Data Sheets

TAT Pages From 9-1773447-9

PDF
English

Flexible, Adhesive-Lined, Polyolefin Heat-Shrinkable Tubing
PDF
English

Product Specifications
Product Specification

Raychem TAT-125 Adhesive Lined Tubing Polyolefin, Flexible, Heat-Shrinkable, Dual Wall
PDF
English

Instruction Sheets
Instruction Sheet (U.S.)

Global Dimensional Life For RAYCHEM Heat Shrink Tubing Standard Size Products (Customer Distribution)

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features

Wall Type Dual

Body Features

Shrink Ratio 2:1

Color Black

Material Crosslinked Polyolefin

Fluid Type Aviation Fuel, Brake Fluid, Chemicals/Solvents, Hydraulic Fluid, Lubricating Oil, Water

Dimensions

Recovered Wall Thickness (Nominal) .74 mm [.029 in]

Expanded Inside Diameter (Min) 9.53 mm [.375 in]

Recovered Inside Diameter (Max) 4.8 mm [.189 in]

Cut Length 38.1 mm [1.5 in]

Usage Conditions

Resistant To Cut-Through, Flexing, Fluids, Mechanical Damage

Operating Temperature Range (°C) -55 – 110

Flammability Flame-Retardant

Shrink Temperature (Min) (°C) 95

Fluid Resistance Moisture/Spray Protection, Splash Protection

Packaging Features

Packaging Method Piece

Other

Product Source US

Statement of Compliance

Statement of Compliance

PDF