



preci-dip

PGA / BGA / PLCC SOCKETS


SERIES
517

517-PP-NNN-XX-XXX111

PGA

Interstitial socket, Solder tail

Pin grid array sockets with interstitial contact rows, solder tails.



TECHNICAL SPECS.:

Insulator	Black glass filled polyester PCT-GF30-FR
Flammability	UL 94V-O
Sleeve	Brass CuZn36Pb3 (C36000)
Contact	Beryllium copper (C17200)
Accepted pin Ø	0.40 to 0.56 mm
Insertion force	0.4 N typ.
Withdrawal force	0.2 N typ. (polished steel gauge Ø 0.46 mm)
Mechanical life	Min. 100 cycles
Rated current	1 A
Contact resistance	Max. 10 m
Dielectric strength	Min. 700 V RMS

ORDERING INFORMATION:

PP Plating code	Sleeve	Clip
87	Tin	Gold flash
83	Tin	Gold 0.75 µm

Replace NNN with the number of poles and XX-XXX with body size and layout numbers as indicated here. For example a 19x19 pin configuration with window and 296 contacts as shown here becomes 517-83-296-19-131111. Options: please consult for availability.- PGA sockets with optional standoffs.

TECHNICAL ASSISTANCE

GENERAL SPECIFICATIONS:

The values listed below are general specs applying for PRECI-DIP PGA, BGA and PLCC sockets. Please see individual catalog page for additional and product specific technical data.

Operating temperature range	-55 ... +125 °C
Climatic category (IEC)	55/125/21
Operating humidity range	annual mean 75 %
Max working voltage	100 VRMS/150 VDC (2.54 mm grid)

PRECI-DIP sockets are recognized by Underwriters Laboratories Inc. and listed under "Connectors for Use in Data, Signal, Control and Power Applications", File Nr. E174442

MECHANICAL CHARACTERISTICS:

Clip retention	Min. 40 N (no displacement under axial force applied)
Contact (sleeve / clip) retention	Min. 3.3 N acc. to MIL-DTL-83734, pt 4.6.4.2

ELECTRICAL CHARACTERISTICS:

Insulation resistance between any two adjacent contacts	Min. 10'000 M at 500 V AC
Capacitance between any two adjacent contacts	Max. 1 pF (PLCC max. 2 pF)
Self inductance per contact	Max. 2 nH

ENVIRONMENTAL CHARACTERISTICS:

The sockets withstand the following environmental tests without mechanical and electrical defects:

- Dry heat steady state IEC 60512-11-9.11i / 60068-2-2.Bb: 125 °C, 16h
- Damp heat cyclic IEC 60512-11-12.11m / 60068-2-30.Db: 25/55 °C, 90 – 100 %rH, 1 cycle of 24 h
- Cold steady state IEC 60512-11-10.11j / 60068-2-1.A: -55 °C, 2 h
- Thermal shock IEC 60512-11-4.11d / 60068-2-14.Na: -55/125 °C, 5 cycles 30 min
- Sinusoidal vibrations IEC 60512-6-4.6d / 60068-2-6.Fc: 10 to 500 Hz, 10 g, 1 octave/min, 10 cycles for each axis
- Shock IEC 60512-6-3.6c / 60068-2-27.Ea: 50 g, 11 ms, 3 shocks in three axis

During the above two tests no contact interruption >50 ns does appear.

- Solderability J-STD-002A, Test A, 245°C, 5 s solder alloy SnAg3.8Cu0.7
- Resistance to soldering heat J-STD-0020C, 260°C, 20 s
- Moisture sensitivity J-STD-020C level 1
- Resistance to corrosion :
 - 1) Salt spray test IEC 60068-2-11.Ka: 48 h
 - 2) Sulfur dioxide (SO₂) test IEC 60068-2-42 Kc: 96 h at 25 ppm SO₂, 25 °C, 75 %rH
 - 3) Hydrogen sulfide (H₂S) test IEC 60068-2-43 Kd: 96 h at 12 ppm H₂S, 25 °C, 75 %rH

SOLDERLESS COMPLIANT PRESS-FIT CHARACTERISTICS:

PRESS-FIT CHARACTERISTICS MEASURED ACC. TO IEC 60352-5

- Press-in force: 90 N max. (at min. hole dia.) / 65 N typ.
- Push-out force: 30 N min. (at max. hole dia.) / 50 N typ.
- Push-out 3rd cycle: 20 N min. (at max. hole dia.)

PCB HOLE DIMENSIONS

- 2.54 mm grid: Finished hole Ø: 1 + 0.09/-0.06 mm | Drilled hole Ø: 1.15 ± 0.02 mm

- Interstitial grid: Finished hole $\varnothing$: $0.7 + 0.09/-0.06$ mm | Drilled hole $\varnothing$: 0.8 ± 0.02 mm

PCB HOLE PLATING

- PCB surface finish: Hole plating
- Tin: 5-15 μm tin over min. 25 μm copper
- Copper: min. 25 μm copper
- Gold over nickel: 0.05-0.2 μm gold over 2.5-5 μm nickel over min. 25 μm copper

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Preci-dip:

[517-87-321-17-101111](#) [517-87-401-19-101111](#) [517-87-391-18-101111](#) [517-87-372-19-111111](#) [517-87-370-19-121111](#) [517-87-369-18-091111](#) [517-83-370-19-121111](#) [517-83-369-18-091111](#) [517-83-365-14-000111](#) [517-83-365-17-091111](#) [517-83-364-17-091111](#) [517-83-428-19-101111](#) [517-83-565-21-111111](#) [517-83-411-20-111111](#) [517-83-403-19-111111](#) [517-83-401-19-101111](#) [517-83-391-18-101111](#) [517-83-372-19-111111](#) [517-83-475-21-121111](#) [517-83-463-19-101111](#) [517-83-429-19-101111](#) [517-83-321-19-121111](#) [517-83-420-19-111111](#) [517-83-419-19-111111](#) [517-83-545-17-000111](#) [517-83-539-20-101111](#) [517-83-529-21-121111](#) [517-83-528-21-121111](#) [517-83-503-22-131111](#) [517-83-293-18-101111](#) [517-83-280-18-101111](#) [517-83-265-12-000111](#) [517-83-325-18-111111](#) [517-83-361-18-101111](#) [517-83-183-14-091111](#) [517-83-321-17-101111](#) [517-83-320-19-131111](#) [517-83-305-18-101111](#) [517-83-304-14-051111](#) [517-83-299-16-091111](#) [517-83-296-19-131111](#) [517-87-429-19-101111](#) [517-87-428-19-101111](#) [517-87-420-19-111111](#) [517-83-559-22-131111](#) [517-87-559-22-131111](#) [517-83-599-54-131111](#) [517-87-529-21-121111](#) [517-87-528-21-121111](#) [517-87-503-22-131111](#) [517-87-475-21-121111](#) [517-87-463-19-101111](#) [517-87-447-20-121111](#) [517-87-685-19-000111](#) [517-87-599-54-131111](#) [517-87-565-21-111111](#) [517-87-403-19-111111](#) [517-87-545-17-000111](#) [517-87-411-20-111111](#) [517-87-280-18-101111](#) [517-87-265-12-000111](#) [517-87-183-14-091111](#) [517-83-685-19-000111](#) [517-87-325-18-111111](#) [517-87-539-20-101111](#) [517-87-320-19-131111](#) [517-87-305-18-101111](#) [517-87-304-14-051111](#) [517-87-299-16-091111](#) [517-87-296-19-131111](#) [517-87-293-18-101111](#) [517-87-365-14-000111](#) [517-87-365-17-091111](#) [517-87-364-17-091111](#) [517-87-361-18-101111](#) [517-87-321-19-121111](#) [517-87-419-19-111111](#)