



H3-TC1-1-13MX+

4.5-3000MHz 50Ω 1:1 Ratio Balun


APPLICATIONS

- Ideally suited for high volume cellular and wireless applications.


FEATURES

- Surface mount
- Impedance ratio: 1:1
- Available on tape and reel
- RoHS compliant and Pb free
- 260°C reflow compatible

DIMENSIONS



Land Pattern



A	B	C
3.81	3.81	2.85
D		
1.27		

E	F	G
4.83	3.30	1.40
H	J	
0.76	1.27	



Unless otherwise stated dimensions are in mm

Tolerance: .xx ±0.25, .xxx ±0.05


ELECTRICAL SPECIFICATIONS@25°C:

Parameters (P#: ENA PORT)	frequency band	Min.	Typ.	Max.	Unit
Port Impedance, Z0 (P1 / P2 / P3)			50/25/25		Ohm
Insertion Loss	4.5-1000MHz		0.6	1.2	dB
	1000-2000MHz		1.7	2.0	dB
	2000-3000MHz		2.3	3.0	dB
Amplitude UnBalance	4.5-1000MHz		0.5	±1.0	dB
	1000-2000MHz		0.5	±1.0	dB
Phase UnBalance	4.5-1000MHz		4	±10	°
	1000-2000MHz		7	±10	°

TEST CURVE




FUNCTIONAL SCHEMATIC



Pin Configuration

Pin No.	Function
1	Primary Dot
2	Primary
3	Secondary
4	Not Connected (ground)
5	Secondary Dot

APPLICATION & TEST CIRCUIT



ABSOLUTE MAXIMUM RATINGS

Parameter	Value
Input Power	250mW MAX
DC Current	30mA MAX
Operating Temperature Range	-55 to 85°C
Storage Temperature Range	-55 to 125°C

Tel: +86-28-85589664

E-mail: mr_li@henglitaitech.com

Web: www.hltchips.com

Address: No.198 Tianqin East Street, Gaoxin West District, Chengdu City

TEST CURVE

