


Item no.: 233-210
Product description: PCB TERMINAL STRIP 2 SOLDER PINS / POLE 10 POLE
PIN SPACING 2.5 MM / 0.098 IN WITH PUSH BUTTONS



Produkt kann von Bild abweichen / product may differ

Packing unit 180 4*45 pieces

RoHS compliant

Product group	4 (Printed Circuit)
Weight	3.95 g
Color	gray
No. of connection Points	10
No. of potentials	10
pole count	10
Height	15.5 mm
Height	0.61 in
Width	27.3 mm
Width	1.075 in
Depth	13.9 mm
Depth	0.547 in
Pin spacing from	2.5 mm
Pin spacing from	0.098 in
Pollution degree	2
Measured voltage EN	160 V
Measured shock voltage	2.5 kV
Current intensity EN	6 A
Pollution degree	2

Measured voltage EN	320 V
Measured shock voltage	2.5 kV
Current intensity EN	6 A



Connection method	CAGE CLAMP® CONNECTION
Cross section [mm²]	0.08 - 0.5 mm²
Wiring method	solid
Cross section [mm²]	0.08 - 0.5 mm²
Cross section [mm²]	0 - 0.25 mm²
Cross section [mm²]	0 - 0.25 mm²
Cross section [AWG]	28 - 20 AWG
Strip length from	5 mm
Strip length to	6 mm
Material group	I



Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
233-210	ABS	04-HG469925/1-PDA	250	4	0,08-0,5
233-210	BV	11915/A0	250	6	0,08-0,5
233-210	CSA	154112-1465035	150	4	28-20
233-210	DNV	E-9215	250	4	0,08-0,5
233-210	GL	17296-00HH	250	4	0,08-0,5
233-210	KEMA	90.6212.01/02	250	6	0,08-0,5
233-210	RMR	11130002	250	4	0,08-0,5
233-210	UR	E45172	150	4	18-28

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected