


REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pluggable miniature power relay in basic design, with power contact, 2 changeover contacts, input voltage 48 V DC

Commercial data

Item number	1109544
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	C460
Product key	CKF935
GTIN	4063151021436
Weight per piece (including packing)	14.24 g
Weight per piece (excluding packing)	14.24 g
Customs tariff number	85364900
Country of origin	AT

REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Technical data

Product properties

Product type	Single relay
Operating mode	100% operating factor
Mechanical service life	3x 10 ⁷ cycles

Data management status

Date of last data management	06.02.2024
Article revision	01

Insulation characteristics

Insulation	Basic insulation
Overvoltage category	III
Pollution degree	3

Electrical properties

Service life electrical	see diagram
Maximum power dissipation for nominal condition	0.4 W
Test voltage (Winding/contact)	5 kV AC (50 Hz, 1 min., winding/contact)
Rated insulation voltage	250 V AC
Rated surge voltage	4 kV

Input data

Coil side

Nominal input voltage U _N	48 V DC
Input voltage range	33.6 V DC ... 108 V DC
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at U _N	8.7 mA
Typical response time	8 ms
Typical release time	6 ms
Coil voltage	48 V DC
Coil resistance	5.5 kΩ ±10 %

Output data

Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgNi
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V (at 10 mA)
Limiting continuous current	8 A

REL-MR-BL- 48DC/21-21 - Single relay



1109544
<https://www.phoenixcontact.com/us/products/1109544>

Maximum inrush current	12 A (20 ms)
Min. switching current	10 mA (At 5 V)
Interrupting rating (ohmic load) max.	190 W (at 24 V DC)
	85 W (at 48 V DC)
	60 W (at 60 V DC)
	44 W (at 110 V DC)
	60 W (at 220 V DC)
Switching capacity	2000 VA (for 250 V AC)
	2 A (at 24 V, DC13)
	1.5 A (at 230 V, AC15)

Connection data

Connection method	Plug / solder connection
-------------------	--------------------------

Dimensions

Dimensional drawing	
Width	12.7 mm
Height	29 mm
Depth	15.7 mm

Material specifications

Color	orange (RAL 2003)
-------	-------------------

Environmental and real-life conditions

Ambient conditions	
Degree of protection	RT II
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

Standards and regulations


Standards/regulations	IEC 60664
	EN 61810-1

Mounting


Mounting type	Plug-in mounting
Mounting position	any

Drawings


Circuit diagram



Diagram




Diagram




- ① DC coils
- ② AC coils


Operating voltage range

Dimensional drawing





Electrical service life



Permissible humidity for operation and storage.


The maximum permissible ambient temperature as specified in the data sheet must be observed.

Area A: Ice buildup at ambient temperatures $\leq 0^{\circ}\text{C}$ must be prevented

Area B: Condensation at ambient temperatures $> 0^{\circ}\text{C}$ must be prevented

On 30 full days that are naturally distributed across an entire year, a humidity level of 95% is permissible at an ambient temperature $\leq 25^{\circ}\text{C}$.

Drilling plan/solder pad geometry



Basic pitch 2.5 mm

REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1109544>



cUL Recognized
Approval ID: FILE E 228652



UL Recognized
Approval ID: FILE E 228652

cULus Recognized

REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Classifications

ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

ETIM

ETIM 9.0	EC001437
----------	----------

UNSPSC

UNSPSC 21.0	39122300
-------------	----------

REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

REL-MR-BL- 48DC/21-21 - Single relay



1109544

<https://www.phoenixcontact.com/us/products/1109544>

Mandatory accessories

ECOR-1-BSC2-RT/2X21 - Relay base

1027546

<https://www.phoenixcontact.com/us/products/1027546>

ECOR-1... relay base, for miniature power relays or miniature switching relays with 1 or 2 changeover contacts, bolt connection, for mounting on NS 35/7,5.



ECOR-1-BSC3/2X21 - Relay base

2907518

<https://www.phoenixcontact.com/us/products/2907518>

ECOR-1... relay base, for miniature power relay or miniature switching relay with 1 or 2 changeover contacts, screw connection, plug-in option for input/interference suppression modules, for mounting on NS 35/7,5



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com