
Thermofit Molded Parts Specification Control Drawing

Part Number : 222A313 thru 355 Boot, 90°, Long Description :

- 1. All dimensions are in $\frac{\text{incres}}{[\text{millimeters}]}$; $\frac{1}{[\text{gms}]}$
- 2. Dimensions appearing in table are as follows:
 - a As Supplied
 - b After Unrestricted Recovery
- Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
- Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
- 5. Weight shown in table of dimensions is based on polyolefin part.






TABLE OF DIMENSIONS												
PART NUMBER	Н			J			Р	R	s	Т	w	Weight
	Min a -3,-4,-25	Min a -12	Max b	Min a -3,-4,-25	Min a -12	Max b	±10% b	Ref b	Ref b	Ref b	±20% b	Nom b
222A313	1.16	1.02	.51	1.16	.65	.32	5.00	1.25	.53	<u>.50</u>	.09	. <u>031</u>
	[29,5]	[25,9]	[13,0]	[29,5]	[16,5]	[8,1]	[127,0]	[31,8]	[13,5]	[12,7]	[2,29]	[14,1]
222A324	1.36	1.23	.61	1.36	.76	<u>.38</u>	5.50	1.50	<u>.64</u>	. <u>75</u>	.09	.040
	[34,5]	[31,2]	[15,5]	[34,5]	[19,3]	[9,7]	[139,7]	[38,1]	[16,3]	[19.1]	[2,29]	[18,1]
222A334	1.44	1.26	.64	1.44	<u>.78</u>	.40	6.00	1.62	<u>.67</u>	<u>.75</u>	.09	. <u>042</u>
	[36,6]	[32,0]	[16,3]	[36,6]	[19,8]	[10,2]	[152,4]	[41,2]	[17,0]	[19,1]	[2,29]	[19,1]
222A345	1.72	1.41	.77	1.72	<u>.92</u>	<u>.48</u>	6.50	1.87	.80	<u>.75</u>	<u>.09</u>	. <u>055</u>
	[43,7]	[35,8]	[19,6]	[43,7]	[23,4]	[12,2]	[165,1]	[47,5]	[20,3]	[19,1]	[2,29]	[25,0]
222A355	2.16	1.74	.96	2.16	1 <u>.14</u>	<u>.60</u>	7.00	2.44	.95	1 <u>.00</u>	.09	. <u>066</u>
	[54,9]	[44,2]	[24,4]	[54,9]	[29,0]	[15,2]	[177 ,8]	[62,0]	[24,1]	[25,4]	[2,29]	[30,0]

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361-6055

Revision: D Date: 4/02/92

Part Number: 222A313 thru 355


Description: Boot, 90°, Long

Thermofit Molded Parts Specification Control Drawing

222A313 thru 355 Part Number : Description: Boot, 90°, Long

COMPATABILITY CHART									
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION				
-3	Polyolefin, Semi-rigid	RT-301	/42; /86	S-1017;S-1048	Adhesive				
-4	Polyolefin, Flexible	RT-1304	/42; /86	S-1017; S-1048	Adhesive				
-12	*VITON, Flexible	RT-1312	N/A						
-25	Elastomer, Fluid Resistant	RT-1325	/42; /86	S-1017; S-1048	Adhesive				

*VITON is a Registered Trademark of Dupont



THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

Raychem

RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025 (415) 361-6055

Revision : D Date: 4/02/92 Part Number :

222A313 thru 355 Description: Boot, 90°, Long

CAD FILE MP92153