






D see data sheet cable

Technical specification:

Rated voltage: IEC 61076-2-101	250 V
Current rating: IEC 61076-2-101	4 A at 40°C
Insulation resistance: IEC 60512	$\geq 100 \text{ M}\Omega$
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperatur range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	≥ 100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	PA6, UL
Coupling nut:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey


Installation specification:

Recommended torque:	0,6 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 13: 36-000220

Contact assignment:

1)	brown
2)	black
3)	blue
PE)	green-yellow

Part no:	Description:	Length L:	Cable:
43-15325	SAL - 12C - RKW3PE - 2 / K1	2m	TPU, UL20549 black, 4x0,34mm ² , Cable: 781-K1340G
43-15326	SAL - 12C - RKW3PE - 3 / K1	3m	
43-15327	SAL - 12C - RKW3PE - 5 / K1	5m	
43-15328	SAL - 12C - RKW3PE - 10 / K1	10m	
43-xxxxx	SAL - 12C - RKW3PE - ... / K1	x	

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant			 dim. in mm		title: Female connector M12x1 angled C-coded	
			date	name		
	tolerance of cable:	L <= 4m: L + 40mm L > 4m: L + 1%		drawn	21.09.11	Mankopf
				appd.	21.09.11	Franz
	general tolerance:	0 ± 0,50mm 0,0 ± 0,25mm 0,00 ± 0,10mm				
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			dwg no: 43K1A1461			
			part no: see table			