

### Catalog No. HS40-400-4

**Description:** HVYWALL HTSHK 3:1 BLK No4-400 48IN

**UPC No** 786210878621

**Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube**

Heavy-Wall Heat-Shrinkable Tubing for Cable Range 2/0 - 350 kcmil, Expanded Diameter 1.5 Inch, Length 48 Inch, 600 Volt, 90 Degrees Continuous Use, Cross-Linked Polyolefin with Thermoplastic Adhesive Liner, Black

Representative Image

Descriptors	
Category	Heat shrinkable tube
Type	Heavy-Wall Heat Shrinkable Tubing
Special Features	Made of thermally stabilized cross-linked polyolefin, enabling a recovered wall thickenss greater than that of the cable jacket replaced.
Specifications	
Voltage Rating	600 V
Color	Black
Classifications	
Brand Name	Shrink-Kon
Dimensions	
Length	48 in
Compliance and Certifications	
RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant
ETIM	
ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thick-walled
Shrink rate	3:1
Inner diameter before heat-shrink	38.1 mm
Inner diameter before heat-shrink	1.5 inch
Inner diameter after heat-shrink	11.938 mm

ETIM	EC000217 Shrink tubing
Inner diameter after heat-shrink	0.47 inch
Nominal diameter inch	1 1/2 inch
Wall thickness after shrinking	3.5566 mm
Wall thickness after shrinking	0.14 inch
Length	1.2192 m
Length	4 ft
Operation temperature	-55-+110 °C
Operation temperature	-67-+230 °F
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y