



B

B




PIN ASSIGNMENT




NOTES:

- CONNECTOR COMPONENTS:
TRANSPARENT DUST COVER
INSIDE MOLDING: PE
STRAIN RELIEF MOLDING: 45P PVC, BLACK
OUTSIDE MOLDING: ABS, BLACK
SHELL PLATING: GOLD FLASH
CONTACT: GOLD PLATING
DISPLAY PORT CABLE UL20276 (28AWG(7/0.127TC)
*1P+D.W+AL+MYLAR)*5+28AWG (7/0.127TC)*5C+
AL/MY+D.W+BD+JACKET PVC COLOR: BLACK
OD: .29±.008 [7.3±0.2]
- ELECTRICAL TESTING:
100% OPEN & SHORT & CONTINUITY WIRE TEST
CONTACT RESISTANCE: 2 OHM(MAX)
INSULATION RESISTANCE: 10M OHM(MIN)
HI-POT TEST: DC 100V/10ms
- PACKAGING:
ONE CABLE PER BAG



P/N	LENGTH
BC-DD003F	36±0.8 [915±20]
BC-DD006F	72±1.2 [1830±30]
BC-DD010F	120±1.6 [3050±40]



THIRD ANGLE PROJECTION
DO NOT SCALE DRAWING
DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE
DIMENSIONS: INCHES [METRIC]
UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±.005 [0.13] ANGLES ARE ± 1°
SHEET NO. 1 OF 1

	206 Van Vorst Street Jersey City, NJ 07302 +1 201 432 0463 http://www.belfuse.com
TITLE: DISPLAY PORT MALE TO DISPLAY PORT MALE CABLE	
DRN BY: JMM	DATE 05/16/19
APPD BY: ADB	DATE 05/29/19
DWG NO. CT999190	REV. A0