

YHV800-2P-90-50M-B

✓ ACTIVE

TE Internal #: YHV800-2P-90-50M-B
Receptacle, Cable-to-Cable / Wire-to-Wire, 2 Position, 23 mm [.905 in] Centerline, Sealable, Orange, Wire & Cable, Power, Cable Mount (Free-Hanging)
[View on TE.com >](#)



Connectors > Automotive Connectors > Automotive Housings



Connector System: **Cable-to-Cable, Wire-to-Wire**
Number of Positions: **2**
Connector & Housing Type: **Receptacle**
Centerline (Pitch): **23 mm [.905 in]**
Sealable: **Yes**

Features

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Cable-to-Cable, Wire-to-Wire
Connector & Housing Type	Receptacle
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing

Configuration Features

Number of Positions	2
Number of Rows	1

Electrical Characteristics

Operating Voltage	650 VDC
-------------------	---------

Body Features

Cable Exit Angle	90°
Primary Product Color	Orange
Connector & Keying Code	B

Contact Features

Contact Size	8mm
--------------	-----



Contact Type	Socket
Mating Pin Diameter	8 mm[.315 in]

Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PA66 GF30
Centerline (Pitch)	23 mm[.905 in]

Dimensions

Connector Height	62.3 mm[2.45 in]
Product Width	97.5 mm[3.84 in]
Product Length	85 mm[3.35 in]

Usage Conditions

Operating Temperature (Max)	140 °C[284 °F]
Operating Temperature Range	-40 – 140 °C[-40 – 284 °F]

Operation/Application

Circuit Application	Power
---------------------	-------

Industry Standards

Degree of Protection	IP6K7, IP6K9K
Compatible With Agency/Standards Products	LV214

Packaging Features

Packaging Quantity	1
Packaging Method	Package

Other

Serviceable	No
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 2141227-2
2POS,PIN DIA 8.0,PIN HSG,ASSY,SLD

Customers Also Bought



TE Part #776434-1
AMPSEAL 16 Housings



TE Part #HDP24-24-14PE
REC, 14P, BLK, E, 4/12/16, P



TE Part #539960-1
AUSZ-WKZ,MICRO TIM.



TE Part #1625890-5
2W SM M/OX 5% 10K

YHV800-2P-90-50M-B

Receptacle, Cable-to-Cable / Wire-to-Wire, 2 Position, 23 mm [.905 in] Centerline, Sealable, Orange, Wire & Cable, Power, Cable Mount (Free-Hanging)



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_YHV800-2P-90-50M-B_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_YHV800-2P-90-50M-B_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_YHV800-2P-90-50M-B_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

HEMS Sample Kit YHV800-2p-90-50m-B

English

Product Specifications

Application Specification

English