






RECOMMENDED LAND PATTERN DIMENSION OF PCB
(RECOMMENDED METAL MASK THICKNESS : 0.15mm)

- NOTES
- 8 HATCHED PARTS : GROUND CIRCUIT.
 - 2 HATCHED PARTS : GROUND CIRCUIT.
 - SMT LEAD-COPLANARITY : 0.1 MAX.
 - THIS PRODUCT HAS NO POLARITY TO PATTERN FOR MOUNTING.
 - MAKE SURE WIDTH OF PATTERN IS WITHIN THAT OF LAND. OR LEAD MAY TOUCH PATTERN. (THIS APPLIES TO HATCHED AREA.)
 - EMBOSS CARRIER TAPE PACKAGE IS APPLIED ON THIS PRODUCT. PLEASE REFER TO THE SHEET 2/2 FOR THE DETAILS.
 - THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

CROSS CUT SECTION - SIGNAL(5:1)







CROSS CUT SECTION - GROUND(5:1)



4	PHOSPHOR BRONZE	TIN-PLATING			
3	PHOSPHOR BRONZE	CONTACT AREA :GOLD 0.1μm min. LEAD AREA :TIN-PLATING 1μm min. UNDER PLATING:NICKL 1μm min.			
2	PHOSPHOR BRONZE	TIN-PLATING	6	POLYESTER	TOP COVER TAPE
1	LCP	BEIGE	5	POLYSTYRENE	EMBOSSED CARRIER TAPE
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 4 : 1	COUNT 1	DESCRIPTION OF REVISIONS DIS-F-00015123	DESIGNED SY. KUDO
HIROSE ELECTRIC CO., LTD.		APPROVED : HS. OKAWA	20101216	DRAWING NO.	EDC-151948-91-22
		CHECKED : HT. YAMAGUCHI	20101215	PART NO.	FX10B-80P/8-SV(91)
		DESIGNED : SY. KAMIGA	20101215	CODE NO.	CL0570-0021-2-91
		DRAWN : HK. SUNADORI	20101213		
					DATE 20220831

DRAWING FOR PACKING(2:1)

REELED DIMENSION (Free)



- NOTES 8 1 REEL : 1000 CONNECTORS.
9 MINIMUM 10 COMPARTMENTS FROM BOTH REEL ENDS REMAIN EMPTY.
10 THIS PRODUCT HAS NO POLARITY TO TAPE AND REEL PACKAGING.
11 THE DIMENSIONS IN PARENTHESES ARE FOR REFERENCE.

HRS

DRAWING NO.	EDC-151948-91-22
PART NO.	FX10B-80P/8-SV(91)
CODE NO.	CL0570-0021-2-91

1/2