

# EVVOSEMI<sup>®</sup>

THINK CHANGE DO



ESD



TVS



MOS



LDO



Diode



Sensor



DC-DC

## Product Specification

▶ Domestic	Part Number	MB05M THRU MB10M
▶ Overseas	Part Number	MB05M THRU MB10M
▶ Equivalent	Part Number	MB05M THRU MB10M


EV is the abbreviation of name EVVO

**SINGLE PHASE 0.8AMP GLASS PASSIVATED BRIDGE RECTIFIER**
**Features**

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0

**Mechanical Data**

- Case: MB-M, molded plastic
- Terminals: plated leads solderable per MIL-STD-202, Method 208
- Polarity: as marked on case
- Mounting position: Any
- Marking: type number
- Lead Free: For RoHS / Lead Free Version,



Dimiensions in inches and (millimeters)

**Maximum Ratings and Electrical Characteristics**

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.





For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	MB05M	MB1M	MB2M	MB4M	MB6M	MB8M	MB10M	UNITS
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
	V <sub>RWM</sub>								
	V <sub>DC</sub>								
RMS Reverse Voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1)@T <sub>A</sub> =40℃ (Note 2)@T <sub>A</sub> =40℃	I <sub>O</sub>	0.5 0.8							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	30							A
Forward Voltage per element @I <sub>F</sub> =0.8A	V <sub>FM</sub>	1.1							V
Peak Reverse Current @T <sub>A</sub> =25℃ At Rated DC Blocking Voltage @T <sub>A</sub> =125℃	I <sub>R</sub>	5.0 500							uA
Typical Junction Capacitance per leg (Note 3)	C <sub>J</sub>	13							pF
Typical Thermal Resistance per leg	R <sub>θJA</sub>	70							℃/W
	R <sub>θJL</sub>	20							
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55to+150							℃

 Note:1. Mounted on glass epoxy PC board with 1.3mm<sup>2</sup> solder pad.

 2. Mounted on aluminum substrate PC board with 1.3mm<sup>2</sup> solder pad.

3. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.



## Disclaimer

EVVOSEMI ("EVVO") reserves the right to make corrections, enhancements, improvements, and other changes to its products and services at any time, and to discontinue any product or service without notice.

EVVO warrants the performance of its hardware products to the specifications applicable at the time of sale in accordance with its standard warranty. Testing and other quality control techniques are used as deemed necessary by EVVO to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

Customers should obtain and confirm the latest product information and specifications before final design, purchase, or use. EVVO makes no warranty, representation, or guarantee regarding the suitability of its products for any particular purpose, nor does EVVO assume any liability for application assistance or customer product design. EVVO does not warrant or accept any liability for products that are purchased or used for any unintended or unauthorized application.

EVVO products are not authorized for use as critical components in life support devices or systems without the express written approval of EVVOSEMI.

The EVVO logo and EVVOSEMI are trademarks of EVVOSEMI or its subsidiaries in relevant jurisdictions. EVVO reserves the right to make changes without further notice to any products herein.