# 1-406525-2 ACTIVE

### Axicom IM

TE Internal #: 1-406525-2

RJ45 Connector, Single Port, 1 x 1, Standard Connector Contact Density, Jack, Cat 5, Inverted - Latch Up, 8 Position, Standard

Profile, Axicom IM

View on TE.com >



Connectors > Modular Jacks & Plugs > RJ45 Connectors



Modular Jack & Plug Interface Type: RJ45

Port Configuration: Single Port
Port Matrix Configuration: 1 x 1

Modular Jacks & Plugs Products: RJ Type Jacks & Plugs

Connector Contact Density: Standard

### **Features**

### **Product Type Features**

Connector Product Type	Connector Assembly
Modular Jack & Plug Interface Type	RJ45
Modular Jacks & Plugs Products	RJ Type Jacks & Plugs
Modular Connector Style	Jack
Grounding Options	None
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Port Configuration	Single Port
Port Matrix Configuration	1 x 1
Connector Contact Density	Standard
Number of Positions	8
Number of Loaded Positions	8
PCB Mount Orientation	Right Angle

## **Body Features**

Combo at Foothers	
Connector Profile	Standard
Modular Jack Latch Orientation	Inverted - Latch Up

#### Contact Features

Contact Underplating Material	Nickel
-------------------------------	--------



	T·
PCB Contact Termination Area Plating Material	Tin
Contact Current Rating (Max)	1.5 A
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Termination Features	
Termination Method to PCB	Through Hole - Solder
Termination Post & Tail Length	2.54 mm[.1 in]
Mechanical Attachment	
Panel Mount Feature	Without
Connector Mounting Type	Board Mount
Housing Features	
Mating Entry Location	Side
Centerline (Pitch)	1.02 mm[.04 in]
Housing Color	Black
Housing Material	High Temperature Thermoplastic
Dimensions	
PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	12.83 mm[.505 in]
Usage Conditions	
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Indicator Type	Not Illuminated
Shielded	No
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Performance Category	Cat 5
Packaging Features	
Packaging Quantity	80
Packaging Method	Box & Tray, Tray



# **Product Compliance**


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts



Also in the Series | Axicom IM






RJ45 Connectors(2)




Signal Relays(154)


# Customers Also Bought



TE Part #1-643077-0 10P MTA100 MOLDED COVER F/T



TE Part #174146-2 040 MULTILOCK I/O CONN 36PASSY



TE Part #1-1623807-9 SQZ5 22R 10% WIRE



TE Part #7-1393243-9 RT424730



TE Part #1571983-3 GDH02STR04=DIP SWITCH



TE Part #215876-1 6/6 PCB MOD.JACK SE



TE Part #338070-6 MICRO-MATCH FEM.SE



TE Part #2-84953-5

1MM FPC HORZ.TOP CONT.ASSY 25P



TE Part #154743-E SMCQ 68 F AB VV 7-03 CL \* 0007 137 E002



# **Documents**

# **Product Drawings**

IMJ,NO SHLD,8P,PCK&PLC TRAY,SN

English

# **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-406525-2\_D.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1-406525-2\_D.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-406525-2\_D.3d\_stp.zip

English

3D PDF

English

**Customer View Model** 

ENG\_CVM\_1-406525-2\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_1-406525-2\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_1-406525-2\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.