# 2170245-1 ACTIVE

### Z-PACK | Z-PACK HM-Zd

TE Internal #: 2170245-1

60 Position, Mating Alignment, Guide Lugs Mating Alignment


Type, 6 Row, 10 Column, PCB Mount Header, Z-PACK HM-Zd, High

Speed Backplane Connectors

View on TE.com >



Connectors > PCB Connectors > Backplane Connectors > High Speed Backplane Connectors



Number of Positions: 60

Row-to-Row Spacing: 1.5 mm [ .059 in ]

Mating Alignment: With

Mating Alignment Type: Guide Lugs

Number of Rows: 6

### **Features**

### **Product Type Features**

Connector System	Board-to-Board		
Connector & Contact Terminates To	Printed Circuit Board		
PCB Connector Assembly Type	PCB Mount Header		
Shroud Style	Partially Shrouded		
Configuration Features			
Pairs per Column	3		

Pairs per Column	3		
Number of Ground Positions	60		
Card Slot Centerline	25.4 mm[1 in]		
Number of Pairs	30		
Number of Signal Positions	60		
Number of Positions	60		
Number of Rows	6		
Number of Columns	10		
PCB Mount Orientation	Vertical		
Guide Location	Unguided		
Floatrical Characteristics			

## Electrical Characteristics

Operating Voltage	250 VAC

## Signal Characteristics



Data Rate	≤12 Gb/s
Body Features	
Shield Material	Phosphor Bronze
Primary Product Color	Gray
Contact Features	
Contact Mating Area Length	5.3 mm[.21 in]
Contact Layout	Matrix
Contact Type	Pin
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze
Contact Current Rating (Max)	.7 A
Termination Features	
Termination Post & Tail Length	1.55 mm[.06 in]
Termination Method to PCB	Through Hole - Press-Fit
Mechanical Attachment	
Mating Alignment	With
Mating Alignment Type	Guide Lugs
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyester - GF
Centerline (Pitch)	2.5 mm[.098 in]
Dimensions	
Connector Length	24.9 mm[.98 in]
Connector Height	13.4 mm[.527 in]
Connector Width	18.85 mm[.742 in]
Row-to-Row Spacing	1.5 mm[.059 in]
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	



	UL Flammability Rating	UL 94V-0		
Packaging Features				
	Packaging Method	Tube		

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**






Also in the Series Z-PACK HM-Zd





Hard Metric Backplane Connectors(1)



High Speed Backplane Connectors(46)



Insertion & Extraction Tools(1)

## Customers Also Bought



TE Part #1-1469491-2 MULTIGIG RT GUIDEPIN, 9MM 2.60



TE Part #120953-4
UPM EXPANDED RCPT ASSEMBLY




TE Part #2170330-1 HMZD+,4PAIRS,10COLS,VERTICAL, ASSEMBLY





TE Part #CONSMA002-L SMA Jack 50 Ohm PCB Through Hole



TE Part #120957-1 UPM EXPANDED PIN ASSEMBLY



TE Part #2-1437186-9 FST-21A-15



TE Part #044847-E STVSKO H M 181 GERA 40A \* EP01 3,50 \* ME TE Part #053298-E STVSKO H F 181 ABGE 40A \* LP-4 1,00 \* FE

## **Documents**

## **Product Drawings**

HMZD+,3PAIRS,10COLS,VERTICAL,ASSEMBLY

English

## **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2170245-1\_A.2d\_dxf.zip

60 Position, Mating Alignment, Guide Lugs Mating Alignment Type, 6 Row, 10 Column, PCB Mount Header, Z-PACK HM-Zd, High Speed Backplane Connectors



English

**Customer View Model** 

ENG\_CVM\_CVM\_2170245-1\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2170245-1\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

**Product Specifications** 

**Application Specification** 

English