

You are here: [Products](#) » [Heatsinks f.cool](#) » [Profile heatsinks and fluid coolers](#) » [Standard extruded heatsinks](#) » [SK 120 ...](#) » [SK 120](#)



▼ Heatsinks f.cool

- ▼ Profile heatsinks and fluid coolers
  - [Standard extruded heatsinks](#)
  - Extruded heatsinks for lock-in retaining spring
  - Extruded heatsinks for PCB mounting
  - Extruded heatsinks for DC/DC converter
  - Retaining springs for transistors
  - U-Extruded heatsinks
  - Die-cast heatsinks
  - Fin coolers
  - Fluid coolers
  - Aluminium flat-, quadrangular-, angled-, U- and T-profiles
- ▶ Heatsinks and active heatsinks for processors
- ▶ Board Level heatsinks
- ▶ Cooling aggregates
- ▶ Accessories for electronic components

▶ Cases f.case

▶ Connectors f.con

## Standard extruded heatsinks

### SK 120 ...

#### SK 120 1000 AL

150 x 40 mm

Data sheet

add to request



Features

Technical Drawing

Service

|                                               |                         |
|-----------------------------------------------|-------------------------|
| <b>thermal resistance <math>R_{th}</math></b> | 1.7 - 1 K/W             |
| <b>surface</b>                                | raw degreased aluminium |
| <b>height</b>                                 | 40 mm                   |
| <b>width B</b>                                | 150 mm                  |
| <b>length</b>                                 | 1000 mm                 |
| <b>plate thickness</b>                        | 4.5 mm                  |