

1078595

https://www.phoenixcontact.com/us/products/1078595

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Coupling housings COM, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 1, straight, 1x M25, height: 68 mm, cable gland: none, Standard

Your advantages

• Good shielding in the event of electromagnetic interference

Commercial data

Item number	1078595
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF59
Product key	BF7APP
Catalog page	Page 653 (C-2-2019)
GTIN	4055626794136
Weight per piece (including packing)	87.8 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85389099
Country of origin	CN



1078595

https://www.phoenixcontact.com/us/products/1078595

Technical data

Product properties

Product type	Housing with locking latch
Housing type	Coupling housings
Product family	HC-COM
Application	Standard
Туре	COM
No. of cable outlets	1
Type of the screw connection	1x M25
Туре	Tall design
Cable outlet	straight
Pg screw connection	none
Data management status	
Article revision	01

Dimensions

Dimensional drawing	45,8
Width	39 mm
Height	68 mm
Length	48.8 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR
Housing material	Die-cast aluminum, salt water resistant
Locking latch material	PA

Mechanical properties

Mechanical data

Type of the screw connection	1x M25
Locking type	Latch

Mounting

Thread type	()

Environmental and real-life conditions



1078595

https://www.phoenixcontact.com/us/products/1078595

Ambient conditions

Degree of protection	IP66
Impact strength	IK06
Ambient temperature (operation)	-40 °C 125 °C





1078595

https://www.phoenixcontact.com/us/products/1078595

Drawings

Dimensional drawing







1078595

https://www.phoenixcontact.com/us/products/1078595

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1078595



cUL RecognizedApproval ID: E255026



UL RecognizedApproval ID: E255026



EAC

Approval ID: RU C-DE.BL08.B.00511

cULus Recognized



1078595

https://www.phoenixcontact.com/us/products/1078595

Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27440202
	ECLASS-12.0	27440202
	ECLASS-13.0	27440202
ETIM		
	ETIM 9.0	EC000437
UNSPSC		

31261500



1078595

https://www.phoenixcontact.com/us/products/1078595

Environmental product compliance

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1078595

https://www.phoenixcontact.com/us/products/1078595

Accessories

HC-COM-BCFS-PLR-BK - Protective cover

1079397

https://www.phoenixcontact.com/us/products/1079397



Protective cover COM, for single locking latch, protective cover material: PA, height: 24.5 mm, seal: yes, Standard, for socket inserts

HC-COM-BCFS-PL-BK - Protective cover

1079396

https://www.phoenixcontact.com/us/products/1079396



Protective cover COM, for single locking latch, protective cover material: PA, height: 24.5 mm, seal: no, Standard, for pin inserts



1078595

https://www.phoenixcontact.com/us/products/1078595

US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

US-EMLP-HA (20X9) CUS - Plastic label

0830995

https://www.phoenixcontact.com/us/products/0830995

Plastic label, Card, can be ordered: by card, white, labeled, can be labeled with: THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70





1078595

https://www.phoenixcontact.com/us/products/1078595

HC-COM-DCFS-PL-BK 100 - Protective cover

1681721

https://www.phoenixcontact.com/us/products/1681721



Protective cover COM, for single locking latch, height: 16 mm, seal: no, Standard, Packing unit: 100 pcs

WP-G HF IP66 M25 BK - Screw connection

3240899

https://www.phoenixcontact.com/us/products/3240899



Cable gland, metric thread, IP66 protection, straight



1078595

https://www.phoenixcontact.com/us/products/1078595

WP-G HF IP69K M25 BK - Screw connection

3240885

https://www.phoenixcontact.com/us/products/3240885



Cable gland, metric thread, IP68/69k protection, straight

WP-GA HF IP66 M25 BK - Screw connection

3240927

https://www.phoenixcontact.com/us/products/3240927

Cable gland, metric thread, IP66 protection, angled





1078595

https://www.phoenixcontact.com/us/products/1078595

WP-GA HF IP69K M25 BK - Screw connection

3240913

https://www.phoenixcontact.com/us/products/3240913

Cable gland, metric thread, IP68/69k protection, angled



WP-GR HF IP66 M25 BK - Screw connection

3240955

https://www.phoenixcontact.com/us/products/3240955

Cable gland, metric thread, IP66 protection, with strain relief





1078595

https://www.phoenixcontact.com/us/products/1078595

WP-GR HF IP69K M25 BK - Screw connection

3240941

https://www.phoenixcontact.com/us/products/3240941



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M25 - Screw connection

3240999

https://www.phoenixcontact.com/us/products/3240999



Cable gland made from PP with metric thread, IP65 protection



1078595

https://www.phoenixcontact.com/us/products/1078595

WP-GT PP HF M25 - Screw connection

3241013

https://www.phoenixcontact.com/us/products/3241013



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M25 - Screw connection

3241048

https://www.phoenixcontact.com/us/products/3241048



Cable gland made from brass with metric thread, IP40 protection



1078595

https://www.phoenixcontact.com/us/products/1078595

WP-GT BRASS M25 - Screw connection

3241034

https://www.phoenixcontact.com/us/products/3241034



Cable gland made from brass with metric thread, rotatable, IP40 protection

WP-G BRASS IP65 M25 - Screw connection

3241062

https://www.phoenixcontact.com/us/products/3241062



Cable gland made from brass with metric thread, IP65 protection

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com