

1617933

https://www.phoenixcontact.com/us/products/1617933

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Panel feed-through, straight, SPEEDCON, M17, number of positions: 8, contact connection type: Pin, Flat gasket, 4x Ø 3.2, shielded: yes, flange dimensions: 25.75 mm x 25.75 mm, degree of protection: IP67, cable diameter range: 11 mm ... 12.7 mm, number of positions: 8, connection method: Crimp connection, series: ST

Commercial data

Item number	1617933
Packing unit	30 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Product key	ABRADJ
Catalog page	Page 167 (NTK-2012)
GTIN	4046356708913
Weight per piece (including packing)	116.9 g
Weight per piece (excluding packing)	111.11 g
Country of origin	DE



1617933

https://www.phoenixcontact.com/us/products/1617933

Technical data

Notes

	Order information:	Order crimp contacts Ø 1 mm separately
Мо	punting	
	Mounting	4x Ø 3.2

Product properties

Product type	Circular connectors (device side)
Series	ST
Application	Signal
Number of positions	8
Connection profile	8
Shielded	yes
Coding	N
Thread type	M17

Dimensions

Housing

Flange dimensions	25.75 mm x 25.75 mm
-------------------	---------------------

Material specifications

Seal material	FPM
Housing material	Metal

Electrical properties

Contact

Contact diameter	1 mm
Max. current	8 A
Nominal voltage U _N	60 V
Overvoltage category	II
Degree of pollution	3
Rated surge voltage	1.5 kV

Connection data

Conductor connection

Connection method	Crimp connection
Contact connection type	Pin

Connector

Туре	straight
Direction of rotation	Standard



1617933

https://www.phoenixcontact.com/us/products/1617933

Cable/line

External cable diameter	11 mm 12.7 mm
-------------------------	---------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C 125 °C
Altitude	3000 m


1617933

https://www.phoenixcontact.com/us/products/1617933




Drawings

Schematic diagram



Installation dimensions

Dimensional drawing



6



https://www.phoenixcontact.com/us/products/1617933





Schematic diagram

8

Connector pin assignment

Dimensional drawing







1617933

https://www.phoenixcontact.com/us/products/1617933

Environmental product compliance

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



1617933

https://www.phoenixcontact.com/us/products/1617933

Accessories

ST-10KP010 - Crimp contact

1618255

https://www.phoenixcontact.com/us/products/1618255



Crimp contact, Pin, turned, Single contact, contact diameter: 1 mm, crimp range: $0.06~\text{mm}^2$... $0.25~\text{mm}^2$, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1~%) item no.: 1243215

ST-10KP035 - Crimp contact

1618458

https://www.phoenixcontact.com/us/products/1618458



Crimp contact, Pin, turned, contact diameter: 1 mm, crimp range: $0.25 \text{ mm}^2 \dots 1 \text{ mm}^2$, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243215



1617933

https://www.phoenixcontact.com/us/products/1617933

ST-Z0016 - Color coding

1617993

https://www.phoenixcontact.com/us/products/1617993

Color coding, color: green



ST-Z0017 - Color coding

1618049

https://www.phoenixcontact.com/us/products/1618049

Color coding, color: orange





1617933

https://www.phoenixcontact.com/us/products/1617933

ST-Z0018 - Color coding

1618050

https://www.phoenixcontact.com/us/products/1618050

Color coding, color: black



Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com