
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


© 2003, Projects Unlimited Inc.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
RATED VOLTAGE (SQUARE WAVE)	6	Vp-p
OPERATING VOLTAGE RANGE	3 ~ 10	Vp-p
RATED CURRENT (MAX)	40	mΑ
COIL RESISTANCE	60±9	ОНМ
MINIMUM SPL @ 10 CM	80	dBA
RESONANT FREQUENCY	2,250±250	Hz
OPERATING TEMPERATURE	-20 ~ +80	°C
STORAGE TEMPERATURE	-30 ~ +85	°C
HOUSING MATERIAL	NORYL	=
TERMINAL MATERIAL	TIN-PLATED COPPER -	
WEIGHT	7	grams


REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
_	RELEASED FROM ENGINEERING	5/1/02	
Α	REVISED TEMP. RANGE ETC.	12/31/02	ر. ن
В	REVISED TO NEW TEMPLATE	6/16/04	R.W.
С	REVISED SPL & FREQUENCY VALUES	10/05/05	B. R.





FILE NAME

AT-202.DWG



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3". APPROVALS DATE DRAWN RABL 5/02 APPROVED S. J. 5/02 SIZE DO NOT SCALE DRAWING

(2)

TRANSDUCER(ELECTRO-MECH) AT-202

Dayton , Ohio

SHEET 1

OF

DRAWING NO. AT-202

projects ® unlimited

SCALE: N.T.S.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PUI Audio: