



Free Height

TE Internal #: 5353185-8
PCB Mount Header, Vertical, Board-to-Board, 100 Position, .6 mm [.024 in] Centerline, Gold, Surface Mount, Signal, Black, Reel, Free Height

[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Header**
PCB Mount Orientation: **Vertical**
Connector System: **Board-to-Board**
Number of Positions: **100**
Centerline (Pitch): **.6 mm [.024 in]**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	100
Board-to-Board Configuration	Parallel

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	200 VAC
Insulation Resistance	2 MΩ
Operating Voltage	50 VAC

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

PCB Contact Termination Area Plating Material Thickness	1 μm[39.37 μin]
Contact Layout	Inline
Mating Tab Width	.3 mm[.012 in]



Mating Tab Thickness	.2 mm[.008 in]
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.2 μm[7.874 μin]
Contact Type	Pin
Contact Current Rating (Max)	.5 A

Termination Features

Square Termination Post & Tail Dimension	.2 mm[.008 in]
Termination Method to PCB	Surface Mount

Mechanical Attachment

PCB Mount Alignment Type	Locating Posts
PCB Mount Retention Type	Solder Peg
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Centerline (Pitch)	.6 mm[.024 in]
Housing Material	High Temperature Thermoplastic

Dimensions

Connector Height	6 mm[.23 in]
Stack Height	6 mm[.236 in]
	.2 in

Usage Conditions

Housing Temperature Rating	High
Operating Temperature Range	-40 – 85 °C[-40 – 185 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------



Packaging Features

Packaging Quantity	800
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


 TE Part # 5353190-8 .6FHR04H,100,S,GIG,08/Sn,TR,NSYes	 TE Part # 3-5353190-8 .6FHR04H,100,S,GIG,30/Sn,TR,NSYes	 TE Part # 5-5316136-8 .6FHR04H,100,S,STD,08/SP,ST,SENo	 TE Part # 5-5353189-8 .6FHR04H,100,S,STD,08/SP,TR,SENo
--	--	---	---



TE Part # 5316136-8
.6FHR04H,100,S,STD,08/SP,ST,NSNo



TE Part # 5316560-8
.6FHR04H,100,S,GIG,08/Sn,HT,SENo



TE Part # 5353189-8
.6FHR04H,100,S,STD,08/SP,TR,NSNo



TE Part # 6318045-8
.6FHR04H,100,S,GIG,08/Sn,TR,NSNo



TE Part # 5-5353729-8
.6FHR04H,200,B,GIG,08/Sn,ST,SENo



TE Part # 5316318-8
.6FHR12H,100,S,GIG,08/Sn,HT,SENo




TE Part # 5316563-8
.6FHR08H,100,S,GIG,08/Sn,ST,NSNo



TE Part # 5353729-8
.6FHR04H,200,B,GIG,08/Sn,ST,NSNo

Also in the Series | Free Height



PCB Headers & Receptacles(752)


Customers Also Bought




TE Part #5-5177986-1
0.8FH,P05H.5,040,30/Sn,TR,SC



TE Part #1-2199119-4
M.2 0.5PITCH 3.2H KEY M 10U" AU



TE Part #2333781-7
MINI IO TO RJ45 CABLE ASSEMBLY, L=4000MM



TE Part #2418344-1
CA,PCIE CEM X16 TO X8 MCIO+SLIVER + PWR



TE Part #2416263-1
OCP STR to MCIO 16X STR





TE Part #2415804-1
MCIO 16X STR to 2XMCIO 8X STR



TE Part #2415816-1
MCIO 8X STR to MCIO 8X STR



TE Part #2415804-2
MCIO 16X STR to 2XMCIO 8X STR



Documents

Product Drawings

.6FHP06H,100,S,STD,08/Sn,TR,NSYes

English

CAD Files

Customer View Model

ENG_CVM_CVM_5353185-8_B.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5353185-8_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5353185-8_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

Fine Pitch Stacking Connectors - 0.6mm Free Height (FH) and GIGA Connectors

English

Product Specifications

Application Specification

English