





A/F无后盖有边弯脚/SMT (5.85)

目錄 MAPX	设 变 内 容 MODIFICATION	日 期 DATE



RBCOMMENDBD P.C.B PATTBRN LAYO UT

NOTES:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy/Steel

Voltage Current Rating:1.5 AMP. 30V AC

Insulation Resistance:1000MΩ Min.

Contact Resistance: 30 MΩ Max.

Dielectric Withstanding Voltage:500W AC

Temperature Range:-35℃ to +85℃

Insulator color: Black/White

Plastic material:PBT/LCP/Others

Shell finish:Nickel plated/Tin-Lead plated

Mechanical:

Mating Force: 3.5KG MAX

Unmating Force:0.7 KG MIN.

Contact finish:

01: Selective Gold Flash

02: Selective Gold 3U”

03: Selective Gold 5U”

04: Selective Gold 15U”

05: Selective Gold 30U”

备注：侧弹分为外弹与内弹

产品图 PRODUCT CHART DWG				深圳市精拓金电子有限公司					
公差一览表 TOLERANCE UNLESS OTHERWISE				单位 UNITS	MM	制图 DRAWING	Z-Y-B	产品料号 PRODUCT PART NO.	903-132A1014S10100
X.	±0.35	X'.	±5°	比例 SCALE	1:1	审核 CHKD	雷永键	产品名称 PRODUCT NO.	AF无后盖弯脚有边内弹改模后铜壳一型5.85PBT白胶SMT 高6.2
.X	±0.25	.X'	±2°					角法 VIEW	版本 VER
.XX	±0.15	.XX'	±1°						
.XXX	±0.10	.XXX'	±0.5°	日期 DATE		核准 APPD	雷永键		A0