



Product: <u>76608TS</u> ☑

MachFlex™, 8 Pr #24 Str TC, SRPVC Ins, OS+TC Brd, PVC Jkt, CMG

Request Sample

# **Product Description**

MachFlex™ for High Flex, 8 Pair 24AWG (10x34) Tinned Copper, SRPVC Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, PVC Outer Jacket, CMG

# **Technical Specifications**

## **Product Overview**

Suitable Applications:	Robotics, Robot, Continuous Flex

# **Construction Details**

#### Conductor

Element	No. of Elements	Size	Stranding	Material
Pair(s)	8	24 AWG	10x34	TC - Tinned Copper

#### Insulation

Element	Material	Nom. Thickness	Nom. Insulation Diameter	Color Code
Pair(s)	PVC - Polyvinyl Chloride	0.010 in (0.25 mm)	0.044 in (1.1 mm)	Black & Red, Black & white, Black & Green, Black & Blue, Black & Brown, Black & Yellow, Black & Orange, Red & Green

# Outer Shield

Shield Type	Material	Coverage	Drainwire Type
Таре	Bi-Laminate (Alum+Poly)	100%	26 AWG (7x34) TC
Braid	Tinned Copper (TC)	85%	

#### Outer Jacket

Separator	Material	Nom. Thickness	Nom. Diameter
Paper Tape	PVC - Polyvinyl Chloride	0.040 in (1.0 mm)	0.385 in
Overall Cabl	le Diameter (Nominal):	0.385 in	

# **Electrical Characteristics**

# Electricals

Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Characteristic Impedence	
30 Ohm/1000ft	23.1 pF/ft (75.8 pF/m)	82 Ohm	

## Voltage

UL Voltage Rating 300 V

# **Mechanical Characteristics**

# Temperature

<b>UL Temperature</b>	Operating
105°C	-10°C To 105°C (Static), 5°C To 105°C (Flexing)

#### Bend Radius

Stationary Min. Installation Min. Flexing Min.

3.85 in (97.8 mm) 5.8 in	5.8 in (150 mm)	
Max. Pull Tension:	61 lbs (28 kg)	
Bulk Cable Weight:	80 lbs/1000ft	

#### **Standards and Compliance**

Environmental Suitability:	Sunlight Resistance	
Flammability / Reaction to Fire:	UL1685 UL Loading, FT4	
NEC / UL Compliance:	uticle 800, CM	
AWM Compliance:	AWM 2661, AWM 10002, AWM I/II A/B	
CEC / C(UL) Compliance:	CMG	
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)	
APAC Compliance:	China RoHS II (GB/T 26572-2011)	

## **History**

Update and Revision:	Revision Number: 0.136 Revision Date: 05-31-2024

## **Part Numbers**

#### Variants

	Item #	Color	Putup Type	UPC
	76608TS 008100	Gray	Reel	612825411673
Ì	76608TS 0081000	Gray	Reel	612825411680

#### © 2024 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.