



- 1.CABLE:UL2725,28AWG(7/0.12mm)X1PAIRS
+24AWG(7/0.2mm)X2C,TIN COPPER
INSULATOR:P FOR 28AWG&PVC 24AWG
SHIELD:AL-FOL+DRAIN WIRE+BRAID
JACKET:PVC,COLOR:GREY,D.I:4.8mm±0.2mm
- 2.CONNECTOR:1 PCS USB A SOLDER TYPE MALE
COLOR:WHITE COLOR
SHELL:NICKEL PLATED
- 3.CONNECTOR:1 PCS USB A SOLDER TYPE FEMALE
SHELL:NICKEL PLATED
- 4.HOOD:MOULDED GREY COLOR
- 5.Fulfill ROHS Guideline
- 6.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

WIRE LIST

P1		P2	
USB A MALE	WIRE COLOR	USB A FEMALE	AWG
1	RED	1	24AWG
2	WHITE	2	1 PAIRS (28AWG)
3	GREEN	3	
4	BLACK	4	24AWG
SHELL	DRAIN	SHELL	

PART NO	CAB-USBAAF-1.8	SHEET NO	1	THIRD ANGLE PROJECTION	
TITLE:USB A MALE TO USB A FEMALE L1.8M,UL2725 CABLE,GREY COLOR				SCALE	N.T.S
				SIZE	A4
				UNIT	
DWN NO	D-CAB-USBAAF-1.8	☒ mm ☐ INCH		APPROVED BY & DATE	

