

**Part Number:** [0003092158](#)  
**Status:** **Planned for Obsolescence**  
**Overview:** [standard .093](#)  
**Description:** 2.36mm (.093") Diameter Standard .093 Pin and Socket Plug Housing, 15 Circuits, 3 Rows

**Documents:**

<a href="#">3D Model</a>	<a href="#">Product Specification PS-1375-002 (PDF)</a>
<a href="#">Drawing (PDF)</a>	<a href="#">Packaging Specification PK-1375-001 (PDF)</a>
<a href="#">Product Specification PS-02-09 (PDF)</a>	<a href="#">RoHS Certificate of Compliance (PDF)</a>
<a href="#">Product Specification PS-1375-001 (PDF)</a>	

**Agency Certification**

CSA	LR19980
UL	E29179

**General**

Product Family	Crimp Housings
Series	<a href="#">1375</a>
Application	Power
Comments	12.5A max. can be achieved when housing is used with 42477 or 42478 terminals
Overview	<a href="#">standard .093</a>
Product Name	Standard .093"

**Physical**

Circuits (maximum)	15
Color - Resin	Natural
Flammability	94V-2
Gender	Dual
Glow-Wire Compliant	No
Material - Resin	Nylon
Number of Rows	3
Packaging Type	Bag
Panel Mount	No
Pitch - Mating Interface	5.03mm (.198")
Stackable	No
Temperature Range - Operating	-40°C to +105°C

**Electrical**

Current - Maximum per Contact	9.5A
-------------------------------	------

**Material Info**

Old Part Number	1375P7
-----------------	--------

**Reference - Drawing Numbers**

Packaging Specification	PK-1375-001
Product Specification	PS-02-09, PS-1375-001, PS-1375-002
Sales Drawing	SD-1375-*



**EU RoHS**  
**ELV and**  
**Compliance**  
**REACH**  
**Contains**  
**Low-Halogen**  
**Not Restricted**

**Need more information?**

Email product manager  
 For a more detailed  
 Compliance information

Please visit our website  
 for non-product related information

**Search**  
[1375S](#)

**Mates**  
[1375r](#)

**Use With**  
[1189 C](#)  
[Termin](#)  
[1377 F](#)  
[Male C](#)  
[Termin](#)  
[Male C](#)  
[, 2870](#)  
[42477](#)